

# Safety Data Sheet

Issue Date 13-Aug-2018

Revision Date 13-Aug-2018

Revision Number 9

## 1. IDENTIFICATION

### Product identifier

**Product Code** 1071-00WHA  
**Product Name** FLUORONAR SG TNEMEC WHITE

### Other means of identification

**Common Name** SERIES 1071, PART A  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
 Flammable liquid and vapor



**Appearance** opaque

**Physical state** liquid

**Odor** Slight

### Precautionary Statements

#### Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool  
 Use explosion-proof electrical/ventilating/lighting/equipment

#### Response

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

##### Other information

May be harmful in contact with skin  
 Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

35.38639 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - <30%
XYLENE	1330-20-7	10 - <30%
ETHYL BENZENE	100-41-4	1 - <10%
AMORPHOUS SILICA	7631-86-9	1 - <10%
N-BUTYL ACETATE	123-86-4	1 - <10%
ALUMINUM HYDROXIDE	21645-51-2	1 - <10%
AMORPH. SILICON DIOXIDE	112926-00-8	1 - <10%
BIS (PENTAMETHYLPYPERIDYL) SEBACATE	41556-26-7	0.1 - <1%
PROPRIETARY	82919-37-7	0.1 - <1%
PETROLEUM SOLVENT (NAPHTHA)	64742-95-6	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Aspiration hazard.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids. Bases. caustic.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m <sup>3</sup>	3000 mg/m <sup>3</sup>
N-BUTYL ACETATE 123-86-4	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	1700 ppm

ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m <sup>3</sup>	-	
AMORPH. SILICON DIOXIDE 112926-00-8	-	TWA: 6 mg/m <sup>3</sup>	

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Safety glasses with side-shields If splashes are likely to occur, wear face-shield.
- Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>	No data available	No data available	
<b>Boiling point / boiling range</b>	118 °C / 244.0 °F		
<b>Flash point</b>	27 °C / 81.0 °F	Pensky Martens - Closed Cup	
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>	No data available	No information available	
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	N/A		
<b>Lower flammability limit</b>	1.0		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	1.45214	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>	No data available	No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>		No data available	
<b>Dynamic viscosity</b>	700 centipoises	approx	
<b>Other Information</b>			
<b>Density</b>	12.11082 lbs/gal		
<b>Volatile organic compounds (VOC)</b>	3.23964 lbs/gal		

<b>content</b>	
<b>Total volatiles weight percent</b>	26.75 %
<b>Total volatiles volume percent</b>	44.68 %
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks. Reacts with air to form peroxides.

### Incompatible materials

Strong oxidizing agents, Acids, Bases, caustic

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )	-	-
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
N-BUTYL ACETATE 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg ( Rat )	-	-
BIS (PENTAMETHYLPIPERIDYL) SEBACATE 41556-26-7	= 2615 mg/kg ( Rat )	-	-
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause cancer. Substances known to be mutagenic to man.

**Sensitization**

No information available.

**Mutagenicity**

May cause genetic defects.

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
XYLENE 1330-20-7		Group 3	-	
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
AMORPHOUS SILICA 7631-86-9		Group 1 Group 3	Known	
AMORPH. SILICON DIOXIDE 112926-00-8		Group 3	-	
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	*	-	-	

**Reproductive effects**

No information available.

**STOT - single exposure**

Eyes, Skin, Lungs

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure

**Target organ effects**

blood, Central nervous system, Gastrointestinal tract, Eyes, kidney, liver, Lungs, respiratory system, Skin.

**Aspiration hazard**

Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity**

35.38639 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

39.488014566 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 7.55 - 11: 96 h Pimephales	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

	mg/L EC50 static	promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
N-BUTYL ACETATE 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
BIS (PENTAMETHYLPYRIDYL) SEBACATE 41556-26-7		0.97: 96 h Lepomis macrochirus mg/L LC50 static	20: 24 h Daphnia magna mg/L EC50
PETROLEUM SOLVENT (NAPHTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
XYLENE 1330-20-7	2.77
ETHYL BENZENE 100-41-4	3.118
N-BUTYL ACETATE 123-86-4	1.81
BIS (PENTAMETHYLPYRIDYL) SEBACATE 41556-26-7	0.37

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical name	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable
N-BUTYL ACETATE	Toxic



123-86-4	
----------	--

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

**Additional information** Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Does Not Comply  
 IECSC Complies  
 KECL Does Not Comply  
 PICCS Complies  
 AICS Complies

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

<b>Chemical name</b>	<b>HAPS Data</b>
XYLENE	
ETHYL BENZENE	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
XYLENE - 1330-20-7	1.0
ETHYL BENZENE - 100-41-4	0.1

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes  
 Fire Hazard Yes  
 Sudden Release of Pressure Hazard No  
 Reactive Hazard No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE	100 lb			X

1330-20-7				
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
N-BUTYL ACETATE 123-86-4	5000 lb			X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
N-BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6	Developmental
IRON OXIDE FUME - 1309-37-1	Group 3
TOLUENE - 108-88-3	Developmental

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
AMORPHOUS SILICA 7631-86-9		X	X
N-BUTYL ACETATE 123-86-4	X	X	X
AMORPH. SILICON DIOXIDE 112926-00-8	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 1 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 3 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 13-Aug-2018

Revision Summary  
 9 4 5 7 10 8 11 14 2 1


**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot

guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 05-Jun-2017

Revision Date 05-Jun-2017

Revision Number 11

## 1. IDENTIFICATION

### Product identifier

**Product Code** B700-1070B  
**Product Name** F700/F701/1070 CONVERTER

### Other means of identification

**Common Name** SERIES 700/701/1070/1071/1072/1078, PART B  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Vapors)	Category 4
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **WARNING**

#### **Hazard statements**

Harmful if inhaled  
May cause an allergic skin reaction  
May cause respiratory irritation. May cause drowsiness or dizziness  
Flammable liquid and vapor



**Appearance** opaque**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Contaminated work clothing should not be allowed out of the workplace  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 If skin irritation or rash occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

89.8 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER	28182-81-2	60 - 100%
PETROLEUM SOLVENT (NAPHTHA) 1,2,4-TRIMETHYLBENZENE	64742-95-6 95-63-6	1 - <10% 1 - <10%
N-BUTYL ACETATE	123-86-4	1 - <10%
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER	822-06-0	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures****General advice**

If symptoms persist, call a physician.

<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Hydrogen cyanide.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Close container after each use. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents, caustic. Water, alcohols, amines, strong bases, metal components, surface active materials.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-BUTYL ACETATE 123-86-4	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	1700 ppm
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	TWA: 0.005 ppm	-	

NIOSH IDLH: *Immediately Dangerous to Life or Health*

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Safety glasses with side-shields. If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>	No data available	No data available
<b>Boiling point / boiling range</b>	72 °C / 162 °F	
<b>Flash point</b>	38 °C / 100.4 °F	
<b>Evaporation rate</b>		Pensky Martens - Closed Cup
<b>Flammability (solid, gas)</b>	No data available	No data available
<b>Flammability Limit in Air</b>		Not applicable
<b>Upper flammability limit</b>	12.3	approximate
<b>Lower flammability limit</b>	0.9	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.12107	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>	875 centipoises	approx

### Other Information

<b>Density</b>	9.34973 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	0.93497 lbs/gal
<b>Total volatiles weight percent</b>	10 %
<b>Total volatiles volume percent</b>	13.9 %
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks. Keep away from children. Amines.

### Incompatible materials

Strong oxidizing agents, caustic, Water, alcohols, amines, strong bases, metal components, surface active materials

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Nitrogen oxides (NO<sub>x</sub>). Hydrocarbons. Hydrogen cyanide.

## 11. TOXICOLOGICAL INFORMATION



**Information on Likely Routes of Exposure**

<b>Inhalation</b>	Contains isocyanate monomer. If subject to spray application, engineering and administrative controls must be instituted to maintain an exposure level below .005ppm. If these controls are not adequate, the use of an air-supplied respirator is mandatory. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. May cause sensitization of susceptible persons.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	May cause sensitization of susceptible persons. Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER 28182-81-2	-	-	= 18500 mg/m <sup>3</sup> ( Rat ) 1 h
PETROLEUM SOLVENT (NAPHTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
N-BUTYL ACETATE 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	= 710 µL/kg ( Rat )	= 593 mg/kg ( Rabbit )	= 0.06 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Skin disorders. Respiratory disorders. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** Avoid repeated exposure. Contains isocyanates. May produce an allergic reaction.  
**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenicity** No information available.  
**Carcinogenicity** There are no known carcinogenic chemicals in this product.  
**Reproductive effects** No information available.  
**STOT - single exposure** Respiratory system, Skin, Central Nervous System (CNS)  
**STOT - repeated exposure** No information available  
**Target organ effects** Central nervous system, respiratory system, Skin.  
**Aspiration hazard** Not applicable.

**Acute Toxicity** 89.8 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects

98.801 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
PETROLEUM SOLVENT (NAPHTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
N-BUTYL ACETATE 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h	72.8: 24 h Daphnia magna mg/L EC50

		Lepomis macrochirus mg/L LC50 static 62: 96 h Leuciscus idus mg/L LC50 static	
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0		26.1: 96 h Brachydanio rerio mg/L LC50 static	

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
N-BUTYL ACETATE 123-86-4	1.81

**Other Adverse Effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239

**California Hazardous Waste Status**

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	CAWAST
N-BUTYL ACETATE 123-86-4	Toxic

### 14. TRANSPORT INFORMATION

**DOT****Proper Shipping Name**

paint in oil Not regulated

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL/NDL	Does not comply
EINECS/ELINCS	Complies
ENCS	Does not comply

IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

**Chemical name** **HAPS Data**  
 HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER - 822-06-0	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes  
 Fire Hazard Yes  
 Sudden Release of Pressure Hazard No  
 Reactive Hazard No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
N-BUTYL ACETATE 123-86-4	5000 lb			X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
N-BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
N-BUTYL ACETATE 123-86-4	X	X	X
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	X	X	

**16. OTHER INFORMATION**

<u>NFPA</u>	Health 2	Flammability 2	Instability 1	Physical hazard *
<u>HMIS (Hazardous Material Information System)</u>	Health 2*	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 05-Jun-2017

Revision Summary  
9 4 5 7 10 8 11 2 14 15 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**