



Safety Data Sheet

Issue Date 14-Aug-2018

Revision Date 13-Aug-2018

Revision Number 6

1. IDENTIFICATION

Product identifier

Product Code 1071V-00WHA
Product Name LOW VOC FLUORONAR TNEMEC WHITE

Other means of identification

Common Name SERIES 1071V, PART A
UN/ID no. 1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
May cause respiratory irritation. May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
Flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor Slight

Precautionary Statements

Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

May be harmful in contact with skin
 Toxic to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET
 Acute Toxicity 29.6266431 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - <30%

FLUOROPOLYMER	-	10 - <30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - <30%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	10 - <30%
tert-BUTYL ACETATE	540-88-5	1 - <10%
AMORPHOUS SILICA	7631-86-9	1 - <10%
ALUMINUM HYDROXIDE	21645-51-2	1 - <10%
AMORPH. SILICON DIOXIDE	112926-00-8	1 - <10%
ZIRCONIUM OXIDE	1314-23-4	0.1 - <1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

- General advice** If symptoms persist, call a physician.
- Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
- Skin contact** Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.
- Inhalation** Remove to fresh air. Oxygen or artificial respiration if needed.
- Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately.
- Self-protection of the first aider** Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Chlorine. Fluorine.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents. Alkaline. Acids. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m ³	-	250 mg/m ³
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	
tert-BUTYL ACETATE 540-88-5	TWA: 50 ppm STEL: 150 ppm	TWA: 200 ppm TWA: 950 mg/m ³	1500 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m ³	3000 mg/m ³
ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m ³	-	
AMORPH. SILICON DIOXIDE 112926-00-8	-	TWA: 6 mg/m ³	
ZIRCONIUM OXIDE 1314-23-4	TWA: 5 mg/m ³	-	25 mg/m ³

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and

general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
Skin and body protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory protection	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	98 °C / 208.0 °F	
Flash point	27 °C / 81.0 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	.8	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.54022	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	1900 centipoises	approx

Other Information

Density	12.84541 lbs/gal
Volatile organic compounds (VOC) content	0.98793 lbs/gal
Total volatiles weight percent	39.22 %
Total volatiles volume percent	50.61 %
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Reacts with air to form peroxides.

Incompatible materials

Strong oxidizing agents, Alkaline, Acids, Bases

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Causes serious eye irritation.
Skin contact	Irritating to skin. May cause sensitization by skin contact.
Ingestion	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)	-	-
BARIUM SULFATE (TOTAL DUST) 7727-43-7	= 307000 mg/kg (Rat)	-	-
tert-BUTYL ACETATE 540-88-5	= 4100 mg/kg (Rat)	> 2 g/kg (Rabbit) > 2000 mg/kg (Rabbit)	> 2230 mg/m ³ (Rat) 4 h > 9482 mg/m ³ (Rat) 4 h
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons.
Mutagenicity May cause genetic defects.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B	-	X

13463-67-7				
AMORPHOUS SILICA 7631-86-9		Group 1 Group 3	Known	
AMORPH. SILICON DIOXIDE 112926-00-8		Group 3	-	

Reproductive effects No information available.
STOT - single exposure Eyes, Central Nervous System (CNS), Skin
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects Central nervous system, Eyes, Lungs, respiratory system, Skin.
Aspiration hazard No information available.

Acute Toxicity 29.6266431 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

33.92748 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
tert-BUTYL ACETATE 540-88-5		296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
tert-BUTYL ACETATE 540-88-5	1.38

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
ACETONE 67-64-1		Included in waste stream: F039		U002
TOLUENE	U220	Included in waste streams:		U220

108-88-3		F005, F024, F025, F039, K015, K036, K037, K149, K151	
----------	--	--	--

14. TRANSPORT INFORMATION

DOT

UN/ID no. 1263
 Proper Shipping Name PAINT
 Hazard Class 3
 Packing Group III
 Emergency Response Guide Number 128

Additional information Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Complies
 ENCS Does Not Comply
 IECSC Complies
 KECL Does Not Comply
 PICCS Does Not Comply
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard Yes
 Chronic Health Hazard Yes
 Fire Hazard Yes
 Sudden Release of Pressure Hazard No
 Reactive Hazard No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances

tert-BUTYL ACETATE 540-88-5				X
--------------------------------	--	--	--	---

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
tert-BUTYL ACETATE 540-88-5	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6	Developmental
AMORPHOUS SILICA - 7631-86-9	Carcinogen
IRON OXIDE FUME - 1309-37-1	Group 3
TOLUENE - 108-88-3	Developmental
DIBUTYLTIN DILAURYL MERCAPTIDE - 1185-81-5	REPRODUCTIVE

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X
tert-BUTYL ACETATE 540-88-5	X	X	X
AMORPHOUS SILICA 7631-86-9		X	X
AMORPH. SILICON DIOXIDE 112926-00-8	X	X	X
ZIRCONIUM OXIDE 1314-23-4		X	

16. OTHER INFORMATION

NFPA Health 2 Flammability 3 Instability 1 Physical hazard *
HMIS (Hazardous Material Information System) Health 2* Flammability 3 Reactivity 1


Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 13-Aug-2018
 Revision Summary
 9 4 5 7 10 8 11 14 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 09-Aug-2016

Revision Date 09-Aug-2016

Revision Number 15

1. IDENTIFICATION

Product identifier

Product Code V700-1070B
Product Name HYDROFLON CONVERTER

Other means of identification

Common Name SERIES V700/V701/1070V/1071V/1072V/1078V, PART B

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO
64120-1372 816-474-3400

Distributor

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203,
Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Harmful if inhaled
Causes skin irritation
Causes serious eye irritation
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction

**Appearance** clear**Physical state** liquid**Odor** odorless**Precautionary Statements****Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 In case of inadequate ventilation wear respiratory protection
 Contaminated work clothing should not be allowed out of the workplace

Response

Get medical advice/attention if you feel unwell
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Storage

Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER	28182-81-2	60 - 100%
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER	822-06-0	0.1 - 1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures**General advice**

If symptoms persist, call a physician.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Foam. Dry chemical. Carbon dioxide.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Nitrogen oxides (NOx). Hydrocarbons.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. Keep people away from and upwind of spill/leak.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE**Precautions for safe handling**

Handling Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling. Do not breathe vapours or spray mist.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Water. Alcohols. Bases. Amines.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	TWA: 0.005 ppm	-	

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	odorless
Appearance	clear	Odor threshold	No information available
Color	No information available		
Property	Values	Remarks	
pH		No data available	

Melting point / freezing point		Literary Reference
Boiling point / boiling range	72 °C / 162 °F	
Flash point	No information available	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.13187	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	700 centipoises	

Other Information

Density	9.41886 lbs/gal
Volatile organic compounds (VOC) content	.000 lbs/gal
Total volatiles weight percent	.0000 %
Total volatiles volume percent	.0000 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

May occur if in contact with moisture, other materials which react with isocyanates, or temperatures above 400 F.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Water, Alcohols, Bases, Amines

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	May cause sensitization by inhalation. Contains isocyanate monomer. If subject to spray application, engineering and administrative controls must be instituted to maintain an exposure level below .005ppm. If these controls are not adequate, the use of an air-supplied respirator is mandatory.
Eye contact	Severely irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER 28182-81-2			= 18500 mg/m ³ (Rat) 1 h
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	= 710 µL/kg (Rat)	= 593 mg/kg (Rabbit)	= 0.06 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Skin disorders. Respiratory disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Avoid repeated exposure. Contains isocyanates. May produce an allergic reaction.
Sensitization May cause sensitization of susceptible persons.
Mutagenicity No information available.
Carcinogenicity There are no known carcinogenic chemicals in this product.
Reproductive effects No information available.
STOT - single exposure No information available
STOT - repeated exposure No information available
Aspiration hazard No information available.

Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

99.5 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0		26.1: 96 h Brachydanio rerio mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media**Other Adverse Effects**

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods**Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT
 Proper Shipping Name PAINT & RELATED MATERIAL

IATA

Additional information Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER	

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER - 822-06-0	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

United States of America

California Prop. 65

This product does not contain any Proposition 65 chemicals

California SCAQMD Rule 443

Does Not Contain Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	X	X	

16. OTHER INFORMATION

NFPA	Health 3	Flammability 0	Instability 1	Physical hazard *
HMIS (Hazardous Material Information System)	Health 3*	Flammability 0	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 09-Aug-2016

Revision Summary
 9 4 5 6 7 10 8 11 14 1 15

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS