

# Safety Data Sheet

Issue Date 26-Oct-2018

Revision Date 26-Oct-2018

Revision Number 2

## 1. IDENTIFICATION

### Product identifier

**Product Code** 1432-0901A  
**Product Name** PROPOLYMER WHITE

### Other means of identification

**Common Name** SERIES 1432, PART A  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372 816-474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203,  
Boisbriand, Quebec Canada J7G 2T3

#### **Emergency telephone number**

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
Suspected of causing cancer  
Causes damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor

**Appearance** paste**Physical state** liquid**Odor** Strong aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

**Other information**

SEE SAFETY DATA SHEET

Very toxic to aquatic life with long lasting effects

Acute Toxicity 55 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
VINYL ESTER RESIN	-	30 - <60%

STYRENE	100-42-5	10 - <30%
UNTREATED GLASS FLAKE	65997-17-3	10 - <30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	1 - <10%
SYNTHETIC AMORPHOUS PYROGENIC SILICA	112945-52-5	1 - <10%
COBALT NAPHTHANATE	61789-51-3	0.1 - <1%
ZIRCONIUM OXIDE	1314-23-4	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If symptoms persist, call a physician.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Call a physician immediately. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
<b>Ingestion</b>	Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician immediately.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

<b>Most important symptoms and effects</b>	May cause redness and tearing of the eyes. Coughing and / or wheezing. May cause skin and eye irritation. May cause drowsiness or dizziness.
<b>Notes to physician</b>	Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide. Foam. Water spray. Cover with dry sand/earth.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Flammable liquid Thermal decomposition can lead to release of irritating gases and vapours

**Hazardous combustion products** Carbon monoxide. Carbon dioxide.

<b>Impact sensitivity</b>	No.
<b>Sensitivity to Static Discharge</b>	May be ignited by heat, sparks or flames.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Burning produces obnoxious and toxic fumes. Avoid run off to waterways and sewers.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment. Keep people away from and upwind of spill/leak.

### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** Pick up and transfer to properly labelled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Use with local exhaust ventilation. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep container tightly closed in a dry and well-ventilated place.

**Incompatible products** Incompatible with strong acids and bases. Incompatible with oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
STYRENE 100-42-5	TWA: 20 ppm STEL: 40 ppm	TWA: 50 ppm TWA: 215 mg/m <sup>3</sup> STEL: 100 ppm STEL: 425 mg/m <sup>3</sup> TWA: 100 ppm Ceiling: 200 ppm	700 ppm
UNTREATED GLASS FLAKE 65997-17-3	TWA: 1 fiber/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	-	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
ZIRCONIUM OXIDE 1314-23-4	TWA: 5 mg/m <sup>3</sup>	-	25 mg/m <sup>3</sup>

#### **Legend**

NIOSH IDLH: *Immediately Dangerous to Life or Health*

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product. Provide readily accessible eye wash stations and safety showers.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tightly fitting safety goggles

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding. When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Strong aromatic
<b>Appearance</b>	paste	<b>Odor threshold</b>	<1 ppm
<b>Color</b>	pigmented		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	> 115 °C / 239 °F	No information available
<b>Flash point</b>	26.11 °C / 79.00 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>	< 1	
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit</b>	1.1%	
<b>Lower flammability limit</b>	6.6%	
<b>Vapor pressure</b>	0.57 kPa	
<b>Vapor density</b>	>1	No data available
<b>Specific gravity</b>	1.31241	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>	>1000 mm <sup>2</sup> /s	@ 40°C
<b>Dynamic viscosity</b>		No data available

### Other Information

<b>Density</b>	10.9324 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	.046 lbs/gal

Total volatiles weight percent .4176 % (nominal)  
 Total volatiles volume percent .6306 % (nominal)  
 Bulk density No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

**Hazardous polymerization** Hazardous polymerization may occur.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Incompatible with strong acids and bases, Incompatible with oxidizing agents

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

**Inhalation** May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause irritation of respiratory tract. Harmful if inhaled.

**Eye contact** Irritating to eyes.

**Skin contact** Irritating to skin.

**Ingestion** Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
STYRENE 100-42-5	= 1000 mg/kg ( Rat )	-	= 11.7 mg/L ( Rat ) 4 h
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )	-	-
SYNTHETIC AMORPHOUS PYROGENIC SILICA 112945-52-5	= 3160 mg/kg ( Rat )	-	-
COBALT NAPHTHANATE 61789-51-3	= 3900 mg/kg ( Rat )	-	-

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** Avoid repeated exposure. May cause adverse liver effects. Contains a known or suspected carcinogen.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
STYRENE 100-42-5		Group 2A	Reasonably Anticipated	X
UNTREATED GLASS FLAKE 65997-17-3		Group 3	-	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
SYNTHETIC AMORPHUS PYROGENIC SILICA 112945-52-5		Group 3	-	
COBALT NAPHTHANATE 61789-51-3		Group 2B	Reasonably Anticipated	X

**Legend:**

- IARC: (International Agency for Research on Cancer)
- Group 2B - Possibly Carcinogenic to Humans
- NTP: (National Toxicity Program)
- Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
- OSHA: (Occupational Safety & Health Administration)
- X - Present

**Reproductive effects** No information available.

**STOT - single exposure** Not classified

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** respiratory system, Central nervous system, liver, Eyes, Lungs, Reproductive System, Skin, kidney.

**Aspiration hazard** No information available.

**Acute Toxicity** 55 % of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

- ATEmix (oral) 1250 mg/kg
- ATEmix (inhalation-dust/mist) 1.93 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Very toxic to aquatic life with long lasting effects

65.0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
STYRENE 100-42-5	1.4: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.72: 96 h Pseudokirchneriella subcapitata mg/L EC50 0.46 - 4.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.15 - 3.2: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	3.24 - 4.99: 96 h Pimephales promelas mg/L LC50 flow-through 19.03 - 33.53: 96 h Lepomis macrochirus mg/L LC50 static 6.75 - 14.5: 96 h Pimephales promelas mg/L LC50 static 58.75 - 95.32: 96 h Poecilia reticulata mg/L LC50 static	3.3 - 7.4: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
STYRENE 100-42-5	2.95

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
HYDROQUINONE 123-31-9		Included in waste stream: K060		
BENZENE 71-43-2	U019	Included in waste streams: F005, F024, F025, F037, F038, F039, K085, K104, K105, K141, K142, K143, K144, K145, K147, K151, K159, K169, K171, K172	0.5 mg/L regulatory level	U019
METHANOL 67-56-1		Included in waste stream: F039		U154

**California Hazardous Waste Status**

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	CAWAST
STYRENE 100-42-5	Toxic Ignitable
COBALT NAPHTHANATE 61789-51-3	Toxic

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

**IATA**

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 ERG Code 128

**IMDG/IMO**

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 EmS No. F-E,S-E,FP 27°

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies



<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does Not Comply
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Chemical name</b>	<b>HAPS Data</b>
STYRENE	
COBALT NAPHTHANATE	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
STYRENE - 100-42-5	0.1
COBALT NAPHTHANATE - 61789-51-3	1.0

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**Clean Water Act**

The following chemicals are listed under the Clean Water Act:

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
STYRENE 100-42-5	1000 lb			X

**CERCLA**

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
STYRENE 100-42-5	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
STYRENE - 100-42-5	Carcinogen
UNTREATED GLASS FLAKE - 65997-17-3	*
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
ETHYLENE GLYCOL - 107-21-1	Developmental
BENZENE - 71-43-2	Carcinogen Developmental Male Reproductive

METHANOL - 67-56-1	Developmental
--------------------	---------------

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
STYRENE 100-42-5	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
COBALT NAPHTHANATE 61789-51-3	X		X
ZIRCONIUM OXIDE 1314-23-4		X	

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 0 Physical hazard -  
**HMIS (Hazardous** Health 2\* Flammability 3 Reactivity 0  
**Material Information**  
**System)**

*Chronic Hazard Star Legend**\* = Chronic Health Hazard***Prepared By**

Tnemec Regulatory Dept: 816-474-3400

**Revision Date**

26-Oct-2018

**Revision Summary**


1 9 4 5 6 7 10 8 11 13 14 15

**Disclaimer**

**For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.**

**To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.**

**End of SDS**



# Safety Data Sheet

Issue Date 13-Jan-2020

Revision Date 13-Jan-2020

Revision Number 4

## 1. IDENTIFICATION

### Product identifier

**Product Code** 1402-0001B  
**Product Name** PROPOLYMER CATALYST

### Other means of identification

**Common Name** SERIES 469-1439, PART B  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Organic Peroxides	Type F
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### Danger

### Hazard statements

Toxic if inhaled  
Causes severe skin burns and eye damage  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Heating may cause a fire  
Flammable liquid and vapor

**Appearance** yellow**Physical state** liquid**Odor** Strong aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep only in original container  
 Keep cool  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment

**Response**

Immediately call a POISON CENTER or doctor/physician  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Immediately call a POISON CENTER or doctor/physician  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Store at temperatures not exceeding 38 °C/ 100 °F. Keep cool  
 Store away from other materials  
 Protect from sunlight  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
CUMENE HYDROPEROXIDE	80-15-9	60 - 100%
CUMYL ALCOHOL	617-94-7	1 - <10%
(1-METHYLETHYL)BENZENE	-	1 - <10%
ACETOPHENONE	98-86-2	1 - <10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Immediate medical attention is required.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
<b>Ingestion</b>	Immediate medical attention is required. Rinse mouth. Drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Remove all sources of ignition.

##### Most important symptoms and effects, both acute and delayed

**Most important symptoms and effects** Causes burns to skin and eyes. MAY CAUSE BLINDNESS. Coughing and / or wheezing.

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Carbon dioxide. Dry chemical. Water spray. Foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Avoid run off to waterways and sewers.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment. Keep people away from and upwind of spill/leak.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** Pick up and transfer to properly labelled containers.

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Use with local exhaust ventilation. Wear personal protective equipment. Do not breathe vapours or spray mist.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store at temperatures not exceeding 38 °C/ 100 °F. Keep cool. Do not store near combustible materials.

**Packaging materials** Keep only in original container.

**Incompatible products** Strong acids. Strong bases. Strong oxidizing agents. Amines. Metals. SALT. Reducing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
(1-METHYLETHYL)BENZENE	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin	900 ppm
ACETOPHENONE 98-86-2	TWA: 10 ppm	-	

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Tightly fitting safety goggles If splashes are likely to occur, wear face-shield.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Strong aromatic
<b>Appearance</b>	yellow	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	> 100 °C / 212 °F	
<b>Flash point</b>	56 °C / 133.00 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>	< 1	
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	NA	
<b>Lower flammability limit</b>	NA	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.03118 1.0324	g/cm3
<b>Water solubility</b>	slightly soluble	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	No data available
<b>Decomposition temperature</b>	> 60° C	
<b>Kinematic viscosity</b>	No information available	No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Molecular weight</b>	No information available
<b>Density</b>	8.60001 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	1.075 lbs/gal
<b>Total volatiles weight percent</b>	12.5 %
<b>Total volatiles volume percent</b>	12.3 %
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY****Reactivity**

Stable under normal conditions

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

Vapors may form explosive mixtures with air.

**Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition. Temperatures above 38°C.

**Incompatible materials**

Strong acids, Strong bases, Strong oxidizing agents, Amines, Metals, SALT, Reducing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	Irritating to respiratory system. May be harmful by inhalation. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Corrosive to the eyes and may cause severe damage including blindness.
<b>Skin contact</b>	Causes burns.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
CUMENE HYDROPEROXIDE 80-15-9	= 382 mg/kg ( Rat )	= 0.126 mL/kg ( Rabbit )	= 220 ppm ( Rat ) 4 h
CUMYL ALCOHOL 617-94-7	= 1300 mg/kg ( Rat )	= 1 mL/kg ( Rabbit ) = 4300 mg/kg ( Rabbit )	-
(1-METHYLETHYL)BENZENE	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h
ACETOPHENONE 98-86-2	= 815 mg/kg ( Rat ) = 900 mg/kg ( Rat )	= 1760 mg/kg ( Rabbit )	> 2.130 mg/L ( Rat ) 8 h

**Information on toxicological effects**

**Symptoms** Avoid repeated exposure. MAY CAUSE BLINDNESS. Causes severe skin burns. Coughing and/ or wheezing.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Causes severe burns.  
**Eye damage/irritation** Risk of serious damage to eyes.  
**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid repeated exposure. Causes burns to skin and eyes. Aspiration hazard.  
**Sensitization** No information available.  
**Mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
(1-METHYLETHYL)BENZENE		Group 2B	Reasonably Anticipated	X

**Reproductive effects** No information available.  
**STOT - single exposure** No information available  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Eyes, respiratory system, Skin, Central nervous system.



**Aspiration hazard** May be harmful if swallowed and enters airways.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

6 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
CUMENE HYDROPEROXIDE 80-15-9	-	3.9: 96 h Oncorhynchus mykiss mg/L LC50 static	7: 24 h Daphnia magna mg/L EC50
(1-METHYLETHYL)BENZENE	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static
ACETOPHENONE 98-86-2	-	162: 96 h Pimephales promelas mg/L LC50 flow-through 155: 96 h Pimephales promelas mg/L LC50 static	-

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
(1-METHYLETHYL)BENZENE	3.55
ACETOPHENONE 98-86-2	1.58

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

#### **Contaminated packaging**

Do not reuse container. Empty containers should be taken to an approved waste handling site for recycling or disposal.

#### **US EPA Waste Number**

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
CUMENE HYDROPEROXIDE 80-15-9				U096
(1-METHYLETHYL)BENZENE				U055
ACETOPHENONE 98-86-2	U004	Included in waste stream: F039		U004

**California Hazardous Waste Status**

Chemical name	CAWAST
CUMENE HYDROPEROXIDE 80-15-9	Toxic Ignitable
(1-METHYLETHYL)BENZENE	Toxic Ignitable

**14. TRANSPORT INFORMATION**

DOT

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

International Inventories

TSCA Complies  
 DSL/NDL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

Chemical name	HAPS Data
(1-METHYLETHYL)BENZENE	
ACETOPHENONE	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
CUMENE HYDROPEROXIDE - 80-15-9	1.0
(1-METHYLETHYL)BENZENE -	1.0
ACETOPHENONE - 98-86-2	1.0

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard Yes

Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
CUMENE HYDROPEROXIDE 80-15-9	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
(1-METHYLETHYL)BENZENE	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ACETOPHENONE 98-86-2	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
(1-METHYLETHYL)BENZENE -	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
CUMENE HYDROPEROXIDE 80-15-9	X	X	X
(1-METHYLETHYL)BENZENE	X	X	X
ACETOPHENONE 98-86-2	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 3	Flammability 2	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 3*	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 13-Jan-2020

Revision Summary  
1 9 4 5 6 7 10 8 11 13 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**