



Safety Data Sheet

Issue Date 28-Aug-2018

Revision Date 11-Mar-2018

Revision Number 5

1. IDENTIFICATION

Product identifier

Product Code F157-01WH
Product Name ENVIRO-CRETETX ASH WHITE

Other means of identification

Common Name SERIES 157
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes eye irritation
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure



Appearance opaque**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray

Response

IF exposed: Call a POISON CENTER or doctor/physician
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician if you feel unwell
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth

Storage

Store locked up
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

Other information

Causes mild skin irritation
 Very toxic to aquatic life with long lasting effects
 Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs
 SEE SAFETY DATA SHEET
 Acute Toxicity 33.93148 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	10 - <30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	1 - <10%
ZINC COMPOUNDS	1314-13-2	1 - <10%
CALCINED KAOLIN	92704-41-1	1 - <10%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	1 - <10%
GLASS OXIDE	65997-17-3	1 - <10%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****General advice**

If symptoms persist, call a physician.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Sulfur oxides. Hydrogen chloride.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink

or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents. Acids. Bases. Alkaline. Amines. Reducing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³ TWA: 50 µg/m ³	50 mg/m ³
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
ZINC COMPOUNDS 1314-13-2	TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³	500 mg/m ³
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m ³	TWA: 15 mg/m ³ TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	
GLASS OXIDE 65997-17-3	TWA: 1 fiber/cm ³ TWA: 5 mg/m ³	-	

NIOSH IDLH: *Immediately Dangerous to Life or Health*

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		
Melting point / freezing point	No data available	
Boiling point / boiling range	100 °C / 212.0 °F	
Flash point	No information available	
Evaporation rate		
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		
Vapor density		
Specific gravity	1.5878	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		
Partition coefficient: n-octanol/water		
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity	4500 centipoises	approx

Other Information

Density	13.24226 lbs/gal
Volatile organic compounds (VOC) content	0.37709 lbs/gal
Total volatiles weight percent	26.84 %
Total volatiles volume percent	43.11 %
Bulk density	No information available

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Acids, Bases, Alkaline, Amines, Reducing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Sulfur oxides. Hydrogen chloride. Carbon oxides. Hydrocarbons.

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure**

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause irritation. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Eye contact	Causes serious eye irritation.
Skin contact	Irritating to skin.
Ingestion	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)	-	-
ZINC COMPOUNDS 1314-13-2	> 5000 mg/kg (Rat)	-	-
CALCINED KAOLIN 92704-41-1	> 2000 mg/kg (Rat)	-	-
BARIUM SULFATE (TOTAL DUST) 7727-43-7	= 307000 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Avoid repeated exposure.

Sensitization

No information available.

Mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
GLASS OXIDE 65997-17-3		Group 3	-	

Reproductive effects

No information available.

STOT - single exposure

Skin, Central Nervous System (CNS), Eyes

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure

Target organ effects

Eyes, Lungs, respiratory system, Skin.

Aspiration hazard

No information available.

Acute Toxicity

33.93148 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

56.39260616246 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
CALCINED KAOLIN 92704-41-1	100: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	1: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media**Other Adverse Effects**

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	CAWAST
ZINC COMPOUNDS 1314-13-2	Toxic

14. TRANSPORT INFORMATION**DOT****Proper Shipping Name**

paint,water base freezable NOT REGULATED

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does Not Comply
ENCS	Does Not Comply
IECSC	Complies
KECL	Does Not Comply
PICCS	Does Not Comply
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
ZINC COMPOUNDS - 1314-13-2	1.0
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC COMPOUNDS 1314-13-2		X		

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
TITANIUM DIOXIDE - 13463-67-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
ETHANOL - 64-17-5	Carcinogen Developmental

California SCAQMD Rule 443

Does Not Contain Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
ZINC COMPOUNDS 1314-13-2	X	X	X
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X

16. OTHER INFORMATION

NFPA	Health 2	Flammability 1	Instability 1	Physical hazard -
HMIS (Hazardous Material Information System)	Health 2	Flammability 1	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 11-Mar-2018
 Revision Summary
 9 4 5 7 10 8 11 14 15

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS