



Safety Data Sheet

Issue Date 21-Aug-2018

Revision Date 24-Jan-2018

Revision Number 12

1. IDENTIFICATION

Product identifier

Product Code S281-00WHA
Product Name TNEME-GLAZE TNEMEC WHITE

Other means of identification

Common Name SERIES 281/210, PART A
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|-------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2A |
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1A |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Flammable Liquids | Category 4 |

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
May cause respiratory irritation. May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
Combustible liquid

**Appearance** opaque**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product

Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

May be harmful if swallowed
 Toxic to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET

Acute Toxicity

1.214E-05 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No | Weight-% |
|-------------------------------|------------|-----------|
| EPOXY RESIN (LER) | 25085-99-8 | 30 - <60% |
| TITANIUM DIOXIDE (TOTAL DUST) | 13463-67-7 | 10 - <30% |
| BARIUM SULFATE (TOTAL DUST) | 7727-43-7 | 10 - <30% |
| NONYLPHENOL | 84852-15-3 | 1 - <10% |
| AMORPHOUS SILICA | 7631-86-9 | 1 - <10% |
| PETROLEUM SOLVENT (NAPTHA) | 64742-95-6 | 0.1 - <1% |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|--|
| General advice | If symptoms persist, call a physician. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately. |
| Inhalation | Remove to fresh air. Oxygen or artificial respiration if needed. |
| Ingestion | If swallowed, do not induce vomiting. Get medical attention immediately. |
| Self-protection of the first aider | Use personal protective equipment. Avoid contact with eyes, skin and clothing. |

Most important symptoms and effects, both acute and delayed

| | |
|---------------------------|------------------------|
| Notes to physician | Treat symptomatically. |
|---------------------------|------------------------|

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Ketones. Silicon.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

| | |
|-----------------------------|--|
| Personal precautions | Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. |
|-----------------------------|--|

Environmental Precautions

| | |
|----------------------------------|---|
| Environmental precautions | Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. |
|----------------------------------|---|

Methods and material for containment and cleaning up

| | |
|--------------------------------|--|
| Methods for containment | Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal. |
|--------------------------------|--|

| | |
|--------------------------------|---|
| Methods for cleaning up | If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated |
|--------------------------------|---|

absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Acids. Bases. Amines. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---|---------------------------|--|------------------------|
| TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7 | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ TWA: 15 mg/m ³ | 5000 mg/m ³ |
| BARIUM SULFATE (TOTAL DUST) 7727-43-7 | TWA: 5 mg/m ³ | TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³ | |
| AMORPHOUS SILICA 7631-86-9 | - | TWA: 6 mg/m ³ | 3000 mg/m ³ |

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|--------|-----------------------|--------------------------|
| Physical state | liquid | Odor | Slight |
| Appearance | opaque | Odor threshold | No information available |
| Color | white | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks</u> |
|---|-------------------------|-----------------------------|
| pH | | |
| Melting point / freezing point | No data available | |
| Boiling point / boiling range | 72 °C / 162 °F | |
| Flash point | 64 °C / 148 °F | Pensky Martens - Closed Cup |
| Evaporation rate | | |
| Flammability (solid, gas) | No data available | |
| Flammability Limit in Air | | |
| Upper flammability limit | N/A | |
| Lower flammability limit | N/A | |
| Vapor pressure | | |
| Vapor density | | |
| Specific gravity | 1.56501 | g/cm3 |
| Water solubility | Insoluble in cold water | |
| Solubility in other solvents | | |
| Partition coefficient: n-octanol/water | | |
| Autoignition temperature | No data available | |
| Decomposition temperature | | |
| Kinematic viscosity | | |
| Dynamic viscosity | 18000 centipoises | approx |

Other Information

| | |
|---|--------------------------|
| Density | 13.0522 lbs/gal |
| Volatile organic compounds (VOC) content | 0.03785 lbs/gal |
| Total volatiles weight percent | 0.29 % |
| Total volatiles volume percent | 0.6 % |
| Bulk density | No information available |

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Contact with water or moist air liberates irritating gas (methanol).

Incompatible materials

Acids, Bases, Amines, Strong oxidizing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Silicon. Ketones. Aldehydes. Carbon oxides. Hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure**Inhalation**

May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause irritation.

| | |
|---------------------|--|
| Eye contact | Causes serious eye irritation. |
| Skin contact | Irritating to skin. May cause sensitization by skin contact. |
| Ingestion | Harmful if swallowed. |

| Chemical name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---|------------------------|-------------------------|------------------------|
| TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| BARIUM SULFATE (TOTAL DUST) 7727-43-7 | = 307000 mg/kg (Rat) | - | - |
| NONYLPHENOL 84852-15-3 | = 1300 mg/kg (Rat) | = 2000 mg/kg (Rabbit) | - |
| AMORPHOUS SILICA 7631-86-9 | = 7900 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 2.2 mg/L (Rat) 1 h |
| PETROLEUM SOLVENT (NAPTHA) 64742-95-6 | = 8400 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 3400 ppm (Rat) 4 h |

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Substances known to impair fertility. Substances known to be mutagenic to man. Skin sensitizer. May cause cancer.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---|-------|--------------------|-------|------|
| TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7 | | Group 2B | - | X |
| AMORPHOUS SILICA 7631-86-9 | | Group 1 Group 3 | Known | |
| PETROLEUM SOLVENT (NAPTHA) 64742-95-6 | * | - | - | |

Reproductive effects Suspected of damaging fertility or the unborn child.

STOT - single exposure Skin, Eyes, Central Nervous System (CNS)

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure

Target organ effects Central nervous system, Eyes, Lungs, Peripheral Nervous System (PNS), respiratory system, Skin, Gastrointestinal tract, liver, Lymphatic System, kidney.

Aspiration hazard Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

Acute Toxicity 1.214E-05 % of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

3.13806 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia |
|---------------------------------|-------------------|----------------------------------|---------------------|
| EPOXY RESIN (LER) 25085-99-8 | 11 mg/L 72 hr | 2 mg/L 96 hr Oncorhynchus mykiss | 1.8 mg/L 48h |

| | | | |
|---|---|---|--|
| NONYLPHENOL 84852-15-3 | 0.36 - 0.48: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 1.3: 72 h Desmodesmus subspicatus mg/L EC50 0.16 - 0.72: 72 h Pseudokirchneriella subcapitata mg/L EC50 static | 0.135: 96 h Pimephales promelas mg/L LC50 flow-through 0.1351: 96 h Lepomis macrochirus mg/L LC50 flow-through | 0.14: 48 h Daphnia magna mg/L EC50 |
| AMORPHOUS SILICA 7631-86-9 | 440: 72 h Pseudokirchneriella subcapitata mg/L EC50 | 5000: 96 h Brachydanio rerio mg/L LC50 static | 7600: 48 h Ceriodaphnia dubia mg/L EC50 |
| PETROLEUM SOLVENT (NAPTHA) 64742-95-6 | | 9.22: 96 h Oncorhynchus mykiss mg/L LC50 | 6.14: 48 h Daphnia magna mg/L EC50 |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

| Chemical name | log Pow |
|---------------------------------|---------|
| EPOXY RESIN (LER) 25085-99-8 | 3 |
| NONYLPHENOL 84852-15-3 | 5.4 |

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

US EPA Waste Number

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|-----------------------------|------|---|------------------------|------------------------|
| XYLENE 1330-20-7 | | Included in waste stream: F039 | | U239 |
| ETHYL BENZENE 100-41-4 | | Included in waste stream: F039 | | |
| PHENOL (SKIN) 108-95-2 | U188 | Included in waste streams: F039, K001, K022, K087 Included in waste stream: K060 | | U188 |
| N-BUTANOL (SKIN) 71-36-3 | | Included in waste stream: F039 | | U031 |
| N-BUTANOL (SKIN) 71-36-3 | | Included in waste stream: F039 | | U031 |

14. TRANSPORT INFORMATION**DOT**

Proper Shipping Name

PAINT & RELATED MATERIAL

Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

| |
|-----------------------------------|
| 15. REGULATORY INFORMATION |
|-----------------------------------|

International Inventories

| | |
|----------------------|-----------------|
| TSCA | Complies |
| DSL/NDSL | Complies |
| EINECS/ELINCS | Does Not Comply |
| ENCS | Does Not Comply |
| IECSC | Complies |
| KECL | Does Not Comply |
| PICCS | Does Not Comply |
| AICS | Does Not Comply |

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

| Chemical name | SARA 313 - Threshold Values |
|---|-----------------------------|
| BARIUM SULFATE (TOTAL DUST) - 7727-43-7 | 1.0 |
| NONYLPHENOL - 84852-15-3 | 1.0 |

SARA 311/312 Hazardous**Categorization**

| | |
|--|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Chemical name | California Prop. 65 |
|--|---------------------|
| TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7 | Carcinogen |
| NONYLPHENOL - 84852-15-3 | * |
| AMORPHOUS SILICA - 7631-86-9 | Carcinogen |
| PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6 | Developmental |
| ETHYL BENZENE - 100-41-4 | Carcinogen |

California SCAQMD Rule 443

Does Not Contain Photochemically Reactive Solvent

State Right-to-Know

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|-------------------------|------------|---------------|--------------|
| TITANIUM DIOXIDE (TOTAL | X | X | X |

| | | | |
|--|---|---|---|
| DUST) 13463-67-7 | | | |
| BARIUM SULFATE (TOTAL DUST) 7727-43-7 | X | X | X |
| AMORPHOUS SILICA 7631-86-9 | | X | X |

16. OTHER INFORMATION

NFPA Health 2 Flammability 1 Instability 1 Physical hazard *

HMIS (Hazardous Health 2* Flammability 1 Reactivity 1

Material Information

System)

Prepared By Tnemec Regulatory Dept: 816-474-3400

Revision Date 24-Jan-2018

Revision Summary

9 4 5 7 10 8 11 14 15 1 13

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 11-Jul-2016

Revision Date 11-Jul-2016

Revision Number 5

1. IDENTIFICATION

Product identifier

Product Code S281-0210B
Product Name S281/S210 CONVERTER

Other means of identification

Common Name SERIES 210/281, PART B

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO
64120-1372 816-474-3400

Distributor

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203,
Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|-------------|
| Acute toxicity - Oral | Category 4 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 1 |
| Skin sensitization | Category 1A |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity (repeated exposure) | Category 1 |

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Harmful if swallowed
Harmful if inhaled
Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure

**Appearance** opaque**Physical state** liquid**Odor** amine**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapors/spray

Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth

Storage

Store locked up
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

May be harmful in contact with skin
 Very toxic to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET

Acute Toxicity

65.8683 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS-No | Weight-% |
|--|-------------|-----------|
| 1,3-BENZENEDIMETHANAMINE, REACTION PRODUCTS WITH STYRENE | 404362-22-7 | 60 - 100% |
| POLYOXYPROPYLENETRIAMINE | 39423-51-3 | 10 - 30% |
| BENZYL ALCOHOL | 100-51-6 | 10 - 30% |
| NONYLPHENOL | 84852-15-3 | 1 - 10% |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|--|
| General advice | If symptoms persist, call a physician. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. |
| Inhalation | Remove to fresh air. Oxygen or artificial respiration if needed. |
| Ingestion | If swallowed, do not induce vomiting. Get medical attention immediately. |
| Self-protection of the first aider | Use personal protective equipment. Avoid contact with eyes, skin and clothing. |

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx). Aldehydes. Ketones.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents. Bases. Acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines
Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|--------------------------|-----------------------|--------------------------|
| Physical state | liquid | Odor | amine |
| Appearance | opaque | Odor threshold | No information available |
| Color | No information available | | |

| | | |
|-----------------|---------------|-------------------|
| Property | Values | Remarks |
| pH | | No data available |

| | | |
|--|--------------------------|--------------------------|
| Melting point / freezing point | | No data available |
| Boiling point / boiling range | 72 °C / 162 °F | |
| Flash point | No information available | |
| Evaporation rate | | No data available |
| Flammability (solid, gas) | | No information available |
| Flammability Limit in Air | | No data available |
| Upper flammability limit | N/A | |
| Lower flammability limit | N/A | |
| Vapor pressure | | No data available |
| Vapor density | | No data available |
| Specific gravity | 1.03469 | g/cm3 |
| Water solubility | Insoluble in cold water | |
| Solubility in other solvents | | No data available |
| Partition coefficient: n-octanol/water | | No data available |
| Autoignition temperature | | No data available |
| Decomposition temperature | | No data available |
| Kinematic viscosity | | No data available |
| Dynamic viscosity | 440 centipoises | |

Other Information

| | |
|--|-----------------|
| Density | 8.61020 lbs/gal |
| Volatile organic compounds (VOC) content | .110 lbs/gal |
| Total volatiles weight percent | 1.2820 % |
| Total volatiles volume percent | 1.2691 % |

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Bases, Acids

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Nitrogen oxides (NOx). Aldehydes. Ketones.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

| | |
|---------------------|---|
| Inhalation | May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. |
| Eye contact | Severely irritating to eyes. |
| Skin contact | Irritating to skin. |
| Ingestion | Harmful if swallowed. |

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|----------------------------|----------------------|-------------------------|------------------------|
| BENZYL ALCOHOL 100-51-6 | = 1230 mg/kg (Rat) | = 2 g/kg (Rabbit) | = 8.8 mg/L (Rat) 4 h |
| NONYLPHENOL 84852-15-3 | = 1300 mg/kg (Rat) | = 2031 mg/kg (Rabbit) | |

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity No information available.

Carcinogenicity There are no known carcinogenic chemicals in this product.

Reproductive effects Suspected of damaging fertility or the unborn child.

STOT - single exposure No information available

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure

Target organ effects Eyes, Skin, respiratory system, Reproductive System.

Aspiration hazard No information available.

Acute Toxicity 65.8683 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects

65.8683 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Component | Toxicity to algae | Toxicity to fish | Toxicity to daphnia |
|----------------------------|---|--|------------------------------------|
| BENZYL ALCOHOL 100-51-6 | 35: 3 h Anabaena variabilis mg/L EC50 | 10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static | 23: 48 h water flea mg/L EC50 |
| NONYLPHENOL 84852-15-3 | 0.16 - 0.72: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.36 - 0.48: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 1.3: 72 h Desmodesmus subspicatus mg/L EC50 | 0.135: 96 h Pimephales promelas mg/L LC50 flow-through 0.1351: 96 h Lepomis macrochirus mg/L LC50 flow-through | 0.14: 48 h Daphnia magna mg/L EC50 |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

| Component | log Pow |
|----------------------------|---------|
| BENZYL ALCOHOL 100-51-6 | 1.1 |
| NONYLPHENOL 84852-15-3 | 5.4 |

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

| |
|----------------------------------|
| 14. TRANSPORT INFORMATION |
|----------------------------------|

DOT

Proper Shipping Name PAINT & RELATED MATERIAL

IATA**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

| |
|-----------------------------------|
| 15. REGULATORY INFORMATION |
|-----------------------------------|

International Inventories

| | |
|----------------------|-----------------|
| TSCA | Complies |
| DSL/NDSL | Complies |
| EINECS/ELINCS | Complies |
| ENCS | Does not comply |
| IECSC | Complies |
| KECL | Complies |
| PICCS | Does not comply |
| AICS | Does not comply |

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

United States of America**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

| Component | SARA 313 - Threshold Values |
|--------------------------|-----------------------------|
| NONYLPHENOL - 84852-15-3 | 1.0 |

SARA 311/312 Hazardous**Categorization**

| | |
|--|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

CERCLAUnited States of AmericaCalifornia Prop. 65

This product does not contain any Proposition 65 chemicals

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

| Component | New Jersey | Massachusetts | Pennsylvania |
|----------------------------|------------|---------------|--------------|
| BENZYL ALCOHOL 100-51-6 | | X | X |

16. OTHER INFORMATION

| | | | | |
|---|-----------|----------------|---------------|-------------------|
| <u>NFPA</u> | Health 3 | Flammability 0 | Instability 1 | Physical hazard * |
| <u>HMIS (Hazardous Material Information System)</u> | Health 3* | Flammability 0 | Reactivity 1 | |

Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 11-Jul-2016

Revision Summary
9 4 5 7 10 8 11 14 15

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS