



# Safety Data Sheet

Issue Date 14-Aug-2018

Revision Date 13-Aug-2018

Revision Number 9

## 1. IDENTIFICATION

### Product identifier

**Product Code** F740-00WHA  
**Product Name** UVX TNEMEC WHITE

### Other means of identification

**Common Name** SERIES 740, PART A  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor

**Appearance** opaque

**Physical state** liquid

**Odor** aromatic

**Precautionary Statements**

**Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Keep cool

**Response**

- IF exposed or concerned: Get medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- If skin irritation or rash occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed
- Keep away from children

**Disposal**

- Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- SEE SAFETY DATA SHEET
- Acute Toxicity 32.73676378 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	30 - <60%

SECONDARY DIAMINES	-	10 - <30%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - <30%
N-BUTYL ACETATE	123-86-4	1 - <10%
ALUMINUM HYDROXIDE	21645-51-2	1 - <10%
AMORPH. SILICON DIOXIDE	112926-00-8	1 - <10%
STYRENE	100-42-5	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Consult a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Chlorine. Fluorine.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or

sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Incompatible with oxidizing agents. Acids. Bases. Alkaline. caustic.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	250 mg/m <sup>3</sup>
N-BUTYL ACETATE 123-86-4	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	1700 ppm
ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m <sup>3</sup>	-	
AMORPH. SILICON DIOXIDE 112926-00-8	-	TWA: 6 mg/m <sup>3</sup>	
STYRENE 100-42-5	TWA: 20 ppm STEL: 40 ppm	TWA: 50 ppm TWA: 215 mg/m <sup>3</sup> STEL: 100 ppm STEL: 425 mg/m <sup>3</sup> TWA: 100 ppm Ceiling: 200 ppm	700 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

<b>9. PHYSICAL AND CHEMICAL PROPERTIES</b>
--

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>	No data available	No data available	
<b>Boiling point / boiling range</b>	118 °C / 244.0 °F		
<b>Flash point</b>	43 °C / 110.0 °F	Pensky Martens - Closed Cup	
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>	No data available	No information available	
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	N/A		
<b>Lower flammability limit</b>	1.7		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	1.54543	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>	No data available	No data available	
<b>Decomposition temperature</b>		None known	
<b>Kinematic viscosity</b>		None known	
<b>Dynamic viscosity</b>	1800 centipoises	approx	
<b>Other Information</b>			
<b>Density</b>	12.88887 lbs/gal		
<b>Volatile organic compounds (VOC) content</b>	0.97702 lbs/gal		
<b>Total volatiles weight percent</b>	20.82 %		
<b>Total volatiles volume percent</b>	27.96 %		
<b>Bulk density</b>	No information available		

<b>10. STABILITY AND REACTIVITY</b>
-------------------------------------

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Reacts with air to form peroxides.

**Incompatible materials**

Incompatible with oxidizing agents, Acids, Bases, Alkaline, caustic

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Chlorine. Fluorine. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	IRRITATING TO RESPIRATORY SYSTEM. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )	-	-
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
N-BUTYL ACETATE 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg ( Rat )	-	-
STYRENE 100-42-5	= 1000 mg/kg ( Rat )	-	= 11.7 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** May cause cancer. Skin sensitizer. Substances known to impair fertility.  
**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
AMORPH. SILICON DIOXIDE 112926-00-8		Group 3	-	
STYRENE 100-42-5		Group 2B	Reasonably Anticipated	X

**Reproductive effects** May damage fertility or the unborn child.

<b>STOT - single exposure</b>	Eyes, Skin, Central Nervous System (CNS)
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure
<b>Target organ effects</b>	blood, Central nervous system, Eyes, hematopoietic system, kidney, liver, Lungs, respiratory system, Skin, Gastrointestinal tract, Peripheral Nervous System (PNS).
<b>Aspiration hazard</b>	No information available.
<b>Acute Toxicity</b>	32.73676378 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Very toxic to aquatic life with long lasting effects

39.63109 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
N-BUTYL ACETATE 123-86-4	674.7: 72 h Desmodemus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
STYRENE 100-42-5	1.4: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.72: 96 h Pseudokirchneriella subcapitata mg/L EC50 0.46 - 4.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.15 - 3.2: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	3.24 - 4.99: 96 h Pimephales promelas mg/L LC50 flow-through 19.03 - 33.53: 96 h Lepomis macrochirus mg/L LC50 static 58.75 - 95.32: 96 h Poecilia reticulata mg/L LC50 static 6.75 - 14.5: 96 h Pimephales promelas mg/L LC50 static	3.3 - 7.4: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
N-BUTYL ACETATE 123-86-4	1.81
STYRENE 100-42-5	2.95

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

#### **US EPA Waste Number**

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes





Chemical name	SARA 313 - Threshold Values
STYRENE - 100-42-5	0.1

**SARA 311/312 Hazardous****Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
N-BUTYL ACETATE 123-86-4	5000 lb			X
STYRENE 100-42-5	1000 lb			X

**CERCLA**

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
N-BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
STYRENE 100-42-5	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
STYRENE - 100-42-5	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen
BENZENE - 71-43-2	Carcinogen Developmental Male Reproductive
SULFURIC ACID - 7664-93-9	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		
N-BUTYL ACETATE 123-86-4	X	X	X
AMORPH. SILICON DIOXIDE 112926-00-8	X	X	X
STYRENE 100-42-5	X	X	X

**16. OTHER INFORMATION**

---

<u>NFPA</u>	Health 3	Flammability 2	Instability 1	Physical hazard *
<u>HMIS (Hazardous Material Information System)</u>	Health 3*	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 13-Aug-2018


Revision Summary  
9 10 11 14 1 4 13 15

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 19-Jul-2018

Revision Date 19-Dec-2017

Revision Number 17

## 1. IDENTIFICATION

### Product identifier

**Product Code** F740-0740B  
**Product Name** UVX CONVERTER

### Other means of identification

**Common Name** SERIES 740/750, PART B  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 In case of inadequate ventilation wear respiratory protection  
 Contaminated work clothing should not be allowed out of the workplace  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Acute Toxicity 23.7141 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
HEXAMETHYLENE DIISOCYANATE HOMOPOLYMER	28182-81-2	60 - 100%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - <30%
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER	822-06-0	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Consult a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Chlorine. Fluorine. Hydrogen cyanide.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

##### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for

proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up**

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Close container after each use. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products**

Strong oxidizing agents. Water, alcohols, amines, strong bases, metal components, surface active materials.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	250 mg/m <sup>3</sup>
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	TWA: 0.005 ppm	-	

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.  
Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>	No data available	No data available
<b>Boiling point / boiling range</b>	139 °C / 282.0 °F	
<b>Flash point</b>	43 °C / 109.0 °F	Seta closed cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>	No data available	No information available
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	N/A	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.20606	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>	310 centipoises	approx

### Other Information

<b>Density</b>	10.05858 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	0 lbs/gal
<b>Total volatiles weight percent</b>	23.71 %
<b>Total volatiles volume percent</b>	21.3 %
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks. Amines.

### Incompatible materials

Strong oxidizing agents, Water, alcohols, amines, strong bases, metal components, surface active materials

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke).

Carbon monoxide. Unidentified organic and inorganic compounds. Hydrocarbons. Carbon oxides. Chlorine. Fluorine. Hydrogen cyanide. Oxides of nitrogen.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause sensitization of susceptible persons. Contains isocyanate monomer. If subject to spray application, engineering and administrative controls must be instituted to maintain an exposure level below .005ppm. If these controls are not adequate, the use of an air-supplied respirator is mandatory.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXAMETHYLENE DIISOCYANATE HOMOPOLYMER 28182-81-2	-	-	= 18500 mg/m <sup>3</sup> ( Rat ) 1 h
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	= 738 mg/kg ( Rat )	= 593 mg/kg ( Rabbit )	= 0.06 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Irritating to eyes and skin. Skin disorders. Respiratory disorders.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** Avoid repeated exposure. Contains isocyanates. May produce an allergic reaction.  
**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenicity** No information available.  
**Carcinogenicity** There are no known carcinogenic chemicals in this product.  
**Reproductive effects** No information available.  
**STOT - single exposure** Eyes, Skin, Central Nervous System (CNS), Respiratory system  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Central nervous system, respiratory system, Skin.  
**Aspiration hazard** No information available.

**Acute Toxicity** 23.7141 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

100 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0		26.1: 96 h Brachydanio rerio mg/L LC50 static	

### Persistence and degradability

No information available.

### Bioaccumulation



No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION**

**DOT**

**Proper Shipping Name** paint in oil NOT REGULATED

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Chemical name</b>	<b>HAPS Data</b>
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical

or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER - 822-06-0	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**California Prop. 65**

None of the ingredients are listed with California Proposition 65.

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	X	X	

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 3	Flammability 2	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 3	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 19-Dec-2017

Revision Summary  
 9 4 5 7 10 8 11 14 15 3

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS