



Safety Data Sheet

Issue Date 14-Aug-2018

Revision Date 13-Aug-2018

Revision Number 12

1. IDENTIFICATION

Product identifier

Product Code F115-00WH
Product Name UNI-BOND DF TNEMEC WHITE

Other means of identification

Common Name SERIES 115
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure



Appearance opaque

Physical state liquid

Odor Slight

Precautionary Statements

Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product

Response

- IF exposed or concerned: Get medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- IF eye irritation persists: Get medical advice/attention
- IF ON SKIN: Wash with plenty of soap and water
- IF skin irritation or rash occurs: Get medical advice/attention
- Wash contaminated clothing before reuse

Storage

- Store locked up
- Keep away from children

Disposal

- Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- Causes mild skin irritation
- Toxic to aquatic life with long lasting effects
- Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).
- Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs
- Contains ethylene glycol monobutyl ether which may cause blood damage based on animal data.
- SEE SAFETY DATA SHEET
- Acute Toxicity 30.11817 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - <30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - <30%
PROPRIETARY PIGMENT (NUISANCE DUST)	-	1 - <10%
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	1 - <10%
PROPRIETARY PIGMENT (NUISANCE DUST)	-	1 - <10%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	1 - <10%
VM&P NAPHTHA	8032-32-4	0.1 - <1%
PETROLEUM DISTILLATES	64742-65-0	0.1 - <1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Ammonia.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.
-----------------------------	--

Environmental Precautions

Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for containment	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
--------------------------------	--

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Acids. Alkaline. Amines. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	TWA: 20 ppm	TWA: 25 ppm TWA: 120 mg/m ³ Skin TWA: 50 ppm TWA: 240 mg/m ³	700 ppm
PROPRIETARY PIGMENT (NUISANCE DUST)	TWA: 1 mg/m ³	-	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³ TWA: 50 µg/m ³	50 mg/m ³
VM&P NAPHTHA 8032-32-4	-	TWA: 300 ppm TWA: 1350 mg/m ³ STEL: 400 ppm STEL: 1800 mg/m ³	

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable

limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	No data available
Boiling point / boiling range	100 °C / 212.0 °F	
Flash point	No information available	
Evaporation rate		No data available
Flammability (solid, gas)	No data available	No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.1	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.39291	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	1000 centipoises	approx

Other Information

Density	11.6169 lbs/gal
Volatile organic compounds (VOC) content	1.1001 lbs/gal
Total volatiles weight percent	39.29 %
Total volatiles volume percent	55.81 %
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Acids, Alkaline, Amines, Strong oxidizing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Ammonia. Carbon oxides. Hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Contact with eyes may cause irritation.
Skin contact	May cause irritation. May cause sensitization by skin contact.
Ingestion	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)	-	-
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
VM&P NAPHTHA 8032-32-4	-	-	= 3400 ppm (Rat) 4 h
PETROLEUM DISTILLATES 64742-65-0	> 15000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 2400 mg/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Contains ethylene glycol monobutyl ether which may cause blood damage based on animal data.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3	-	
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	A3	Group 3	-	
PROPRIETARY PIGMENT (NUISANCE DUST)		Group 3	-	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
PETROLEUM DISTILLATES 64742-65-0	A2	Group 1	Known	

Reproductive effects Suspected of damaging fertility or the unborn child.

STOT - single exposure No information available

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects blood, Central nervous system, Central Vascular System (CVS), Eyes, hematopoietic system, kidney, liver, Lungs, respiratory system, Skin.

Aspiration hazard No information available.

Acute Toxicity 30.11817 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

69.83527 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2		2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
VM&P NAPHTHA 8032-32-4	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50		
PETROLEUM DISTILLATES 64742-65-0		5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	0.81

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name

PAINT & RELATED MATERIAL water base freezable

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Does Not Comply
EINECS/ELINCS	Does Not Comply
ENCS	Does Not Comply
IECSC	Does Not Comply
KECL	Does Not Comply
PICCS	Does Not Comply
AICS	Does Not Comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
ETHYLENE GLYCOL MONOBUTYL ETHER	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
ETHYLENE GLYCOL MONOBUTYL ETHER - 111-76-2	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
ETHYLENE GLYCOL MONOBUTYL ETHER - 111-76-2	Developmental
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
TOLUENE - 108-88-3	Developmental
PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6	Developmental
ETHYLENE GLYCOL - 107-21-1	Developmental
ETHYL BENZENE - 100-41-4	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	X	X	X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
VM&P NAPHTHA 8032-32-4	X		X

16. OTHER INFORMATION

NFPA Health 2 Flammability 0 Instability 0 Physical hazard *
HMIS (Hazardous Material Information System) Health 2* Flammability 0 Reactivity 0

Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 13-Aug-2018
Revision Summary
 4 5 7 10 8 9 11 14 15

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS