



Safety Data Sheet

Issue Date 28-Aug-2018

Revision Date 23-May-2018

Revision Number 7

1. IDENTIFICATION

Product identifier

Product Code L140-00WHA
Product Name POTA-POX PLUS TNEMEC WHITE

Other means of identification

Common Name SERIES L140, PART A
UN/ID no. 1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
May damage fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 Flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor aromatic

Precautionary Statements

Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Keep cool

Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

May be harmful in contact with skin
 Harmful to aquatic life with long lasting effects
 Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).
 Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs
 SEE SAFETY DATA SHEET

Acute Toxicity

23.9243 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - <30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - <30%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - <30%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	10 - <30%
MODIFIED CYCLOALIPHATIC POLYAMINE	68953-36-6	1 - <10%
BENZYL ALCOHOL	100-51-6	1 - <10%
N-BUTANOL (SKIN)	71-36-3	1 - <10%
ISOPHORONE DIAMINE	2855-13-2	1 - <10%
AMORPHOUS SILICA	7631-86-9	1 - <10%
1,2,4-TRIMETHYLBENZENE	95-63-6	0.1 - <1%
ALUMINUM HYDROXIDE	21645-51-2	0.1 - <1%
ZIRCONIUM OXIDE	1314-23-4	0.1 - <1%
1,3,5-TRIMETHYLBENZENE	108-67-8	0.1 - <1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - <1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Aldehydes. Chlorine. Fluorine.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents. Acids. Bases. Cleaning solutions such as Chromerge and Aqua Regia.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m ³	-	250 mg/m ³
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³ TWA: 50 µg/m ³	50 mg/m ³
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m ³	1400 ppm

		TWA: 100 ppm TWA: 300 mg/m ³ TWA: 6 mg/m ³	
AMORPHOUS SILICA 7631-86-9	-		3000 mg/m ³
ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m ³	-	
ZIRCONIUM OXIDE 1314-23-4	TWA: 5 mg/m ³	-	25 mg/m ³
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

Appropriate engineering controls**Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	aromatic
Appearance	opaque	Odor threshold	No information available
Color	No information available		
Property	Values	Remarks	
pH		No data available	
Melting point / freezing point	No data available	No data available	
Boiling point / boiling range	116 °C / 241.0 °F		
Flash point	37 °C / 98.0 °F	Pensky Martens - Closed Cup	
Evaporation rate		No data available	
Flammability (solid, gas)	No data available	Not applicable	
Flammability Limit in Air		No data available	
Upper flammability limit	N/A		
Lower flammability limit	1.4		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	1.77219	g/cm ³	
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature	No data available	No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	

Dynamic viscosity 1000 centipoises approx

Other Information

Density 14.78003 lbs/gal
Volatile organic compounds (VOC) content 1.2162 lbs/gal
Total volatiles weight percent 24.14 %
Total volatiles volume percent 36.77 %
Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Epoxy constituents.

Incompatible materials

Strong oxidizing agents, Acids, Bases, Cleaning solutions such as Chromerge and Aqua Regia

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Chlorine. Fluorine. Oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

Eye contact Causes serious eye damage.

Skin contact Irritating to skin. May cause sensitization by skin contact.

Ingestion Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)	-	-
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg (Rat)	= 2 g/kg (Rabbit)	= 8.8 mg/L (Rat) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg (Rat) = 790 mg/kg (Rat)	= 3400 mg/kg (Rabbit) = 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
ISOPHORONE DIAMINE 2855-13-2	= 1030 mg/kg (Rat)	-	-
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
1,2,4-TRIMETHYLBENZENE	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h

95-63-6			
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg (Rat)	-	-
1,3,5-TRIMETHYLBENZENE 108-67-8	= 5000 mg/kg (Rat)	-	= 24 g/m ³ (Rat) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5 g/kg (Rat)	= 12.18 g/kg (Rabbit) = 14100 µL/kg (Rabbit)	= 5984 ppm (Rat) 6 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Substances known to impair fertility. Substances known to be mutagenic to man. Skin sensitizer.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3	-	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
AMORPHOUS SILICA 7631-86-9		Group 1 Group 3	Known	
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3	-	

Reproductive effects Suspected of damaging fertility or the unborn child.

STOT - single exposure Eyes, Skin, Central Nervous System (CNS)

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure

Target organ effects

Central nervous system, Central Vascular System (CVS), Eyes, Lungs, respiratory system, Skin.

Aspiration hazard No information available.

Acute Toxicity 23.9243 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

25.997917609582 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	460: 96 h Pimephales promelas mg/L LC50 static 10: 96 h Lepomis macrochirus mg/L LC50 static	23: 48 h water flea mg/L EC50
N-BUTANOL (SKIN) 71-36-3	500: 72 h Desmodemus subspicatus mg/L EC50 500: 96 h Desmodemus subspicatus mg/L EC50	1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1740: 96 h	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50

		Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static	
ISOPHORONE DIAMINE 2855-13-2	37: 72 h Desmodemus subspicatus mg/L EC50	110: 96 h Leuciscus idus mg/L LC50 semi-static	14.6 - 21.5: 48 h Daphnia magna mg/L EC50 semi-static 42: 24 h Daphnia magna mg/L EC50
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
1,3,5-TRIMETHYLBENZENE 108-67-8		3.48: 96 h Pimephales promelas mg/L LC50	50: 24 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
BENZYL ALCOHOL 100-51-6	1.1
N-BUTANOL (SKIN) 71-36-3	0.785
ISOPHORONE DIAMINE 2855-13-2	0.79
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
FORMALDEHYDE 50-00-0	U122	Included in waste streams: K009, K010, K038, K040, K156, K157		U122
CUMENE (SKIN) 98-82-8				U055

Chemical name	CAWAST
N-BUTANOL (SKIN) 71-36-3	Toxic

14. TRANSPORT INFORMATION

DOT

UN/ID no.	1263
Proper Shipping Name	PAINT
Hazard Class	3
Packing Group	III
Emergency Response Guide Number	128

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does Not Comply
IECSC	Complies
KECL	Does Not Comply
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
BENZENE, 1,3-DIMETHYL	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
N-BUTANOL (SKIN) - 71-36-3	1.0
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
BENZENE, 1,3-DIMETHYL 108-38-3				X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
AROMATIC HYDROCARBON MIXTURE - 64742-95-6	*
P-P'-ISOPROPYLIDENEDIPHENOL - 80-05-7	Female Reproductive
BENZENE, 1,3-DIMETHYL - 108-38-3	*
ETHYL BENZENE - 100-41-4	Carcinogen
FORMALDEHYDE - 50-00-0	Carcinogen
BENZENE, 1,2-DIMETHYL - 95-47-6	*
BENZENE, 1,4-DIMETHYL - 106-42-3	*
CUMENE (SKIN) - 98-82-8	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
BENZYL ALCOHOL 100-51-6		X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ISOPHORONE DIAMINE 2855-13-2	X		
AMORPHOUS SILICA 7631-86-9		X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
ZIRCONIUM OXIDE 1314-23-4		X	
1,3,5-TRIMETHYLBENZENE 108-67-8		X	
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

16. OTHER INFORMATION

NFPA	Health 2	Flammability 3	Instability 1	Physical hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 23-May-2018


Revision Summary
9 4 5 7 10 8 11 14 15 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 28-Aug-2018

Revision Date 02-Jul-2015

Revision Number 4

1. IDENTIFICATION

Product identifier

Product Code L140-0140B
Product Name POTA-POX PLUS CONVERTER

Other means of identification

Common Name SERIES L140/L140F, PART B
UN/ID no. 1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400

Distributor

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 Flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor aromatic

Precautionary Statements

Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool
 Use explosion-proof electrical/ventilating/lighting/equipment

Response

IF exposed or concerned: Get medical advice/attention
 specific treatment
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

Other information

May be harmful in contact with skin
 Toxic to aquatic life with long lasting effects
 Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).
 Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs

SEE SAFETY DATA SHEET

Acute Toxicity

17.01764197 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
TALC (RESPIRABLE DUST)	14807-96-6	30 - <60%
EPOXY RESIN (LER)	25085-99-8	10 - <30%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - <30%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	1 - <10%
tert-BUTYL ACETATE	540-88-5	1 - <10%
AROMATIC HYDROCARBON MIXTURE	64742-95-6	0.1 - <1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - <1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures**

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Acids. Bases. Amines. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m ³	-	250 mg/m ³
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³ TWA: 50 µg/m ³	50 mg/m ³
tert-BUTYL ACETATE 540-88-5	TWA: 50 ppm STEL: 150 ppm	TWA: 200 ppm TWA: 950 mg/m ³	1500 ppm
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV).

Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
Skin and body protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Respiratory protection	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	aromatic
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		
Melting point / freezing point	No data available	
Boiling point / boiling range	98 °C / 208.0 °F	
Flash point	35 °C / 95.0 °F	Pensky Martens - Closed Cup
Evaporation rate		
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		
Vapor density		
Specific gravity	1.46987	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		
Partition coefficient: n-octanol/water		
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity	1700 centipoises	approx

Other Information

Density	12.25872 lbs/gal
Volatile organic compounds (VOC) content	0.28741 lbs/gal
Total volatiles weight percent	25.9 %
Total volatiles volume percent	31.65 %
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Amines.

Incompatible materials

Acids, Bases, Amines, Strong oxidizing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Chlorine. Fluorine.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Eye contact	Causes serious eye irritation.
Skin contact	Irritating to skin. May cause sensitization by skin contact.
Ingestion	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
tert-BUTYL ACETATE 540-88-5	= 4100 mg/kg (Rat)	> 2 g/kg (Rabbit) > 2000 mg/kg (Rabbit)	> 2230 mg/m ³ (Rat) 4 h > 9482 mg/m ³ (Rat) 4 h
AROMATIC HYDROCARBON MIXTURE 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5 g/kg (Rat)	= 12.18 g/kg (Rabbit) = 14100 µL/kg (Rabbit)	= 5984 ppm (Rat) 6 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Substances known to impair fertility. Substances known to be mutagenic to man. Skin sensitizer.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3	-	
CRYSTALLINE SILICA	A2	Group 1	Known	X

(QUARTZ) 14808-60-7				
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3	-	

Reproductive effects Suspected of damaging fertility or the unborn child.
STOT - single exposure Skin, Central Nervous System (CNS), Eyes
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects Central nervous system, Central Vascular System (CVS), Eyes, Lungs, respiratory system, Skin.
Aspiration hazard No information available.

Acute Toxicity 17.01764197 % of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document .

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

17.72408 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
tert-BUTYL ACETATE 540-88-5		296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	
AROMATIC HYDROCARBON MIXTURE 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
EPOXY RESIN (LER) 25085-99-8	3
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
tert-BUTYL ACETATE 540-88-5	1.38
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert

absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
XYLENE 1330-20-7		Included in waste stream: F039		U239
CUMENE (SKIN) 98-82-8				U055

14. TRANSPORT INFORMATION

DOT

UN/ID no.	1263
Proper Shipping Name	PAINT
Hazard Class	3
Packing Group	III
Emergency Response Guide Number	128

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does Not Comply
ENCS	Does Not Comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
BENZENE, 1,3-DIMETHYL	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

SARA 311/312 Hazardous**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
tert-BUTYL ACETATE 540-88-5				X
BENZENE, 1,3-DIMETHYL 108-38-3				X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
tert-BUTYL ACETATE 540-88-5	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
AROMATIC HYDROCARBON MIXTURE - 64742-95-6	*
BENZENE, 1,3-DIMETHYL - 108-38-3	*
ETHYL BENZENE - 100-41-4	Carcinogen
BENZENE, 1,4-DIMETHYL - 106-42-3	*
BENZENE, 1,2-DIMETHYL - 95-47-6	*
CUMENE (SKIN) - 98-82-8	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
tert-BUTYL ACETATE 540-88-5	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

16. OTHER INFORMATION

NFPA	Health 2	Flammability 3	Instability 1	Physical hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 3	Reactivity 1	

Prepared By
Revision Date
Revision Summary

Tnemec Regulatory Dept: 816-474-3400
02-Jul-2015

9 4 5 7 10 8 11 14

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS