



# Safety Data Sheet

Issue Date 19-Jun-2015

Revision Date 19-Jun-2015

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

Product Code F130-0130A  
Product Name ENVIROFILL PART A

### Other means of identification

Common Name SERIES 130 PART A

### Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.  
Uses advised against Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

Manufacturer Address  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

### Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400  
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2

### Label elements

### EMERGENCY OVERVIEW

#### Danger

#### Hazard statements

Causes severe skin burns and eye damage  
Suspected of causing cancer  
May be corrosive to metals



Appearance opaque

Physical state liquid

Odor Slight

**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Wash face, hands and any exposed skin thoroughly after handling

**Response**

Immediately call a POISON CENTER or doctor/physician  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Immediately call a POISON CENTER or doctor/physician  
 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Storage**

Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Acute Toxicity 51.64550682 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
COAL FIRED FLY ASH BI-PRODUCT	68131-74-8	10 - 30%
TALC (RESPIRABLE DUST)	14807-96-6	1 - 10%
ETHYLENE GLYCOL	107-21-1	1 - 10%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	1 - 10%
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE	25265-77-4	1 - 10%
NONIONIC SURFACTANT	9036-19-5	1 - 10%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.

**Self-protection of the first aider** Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Oxides of nitrogen. Hydrocarbons. Formaldehyde.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Acids. Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	TWA: 1 mg/m <sup>3</sup>	-	100 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>
ETHYLENE GLYCOL 107-21-1	Ceiling: 100 mg/m <sup>3</sup>	Ceiling: 50 ppm Ceiling: 125 mg/m <sup>3</sup>	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
- Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	72 °C / 162 °F		
<b>Flash point</b>	No information available		
<b>Evaporation rate</b>		No data available	

<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	.6	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.01901	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>	1900 centipoises	approx

**Other Information**

<b>Density</b>	8.47970 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	.780 lbs/gal
<b>Total volatiles weight percent</b>	39.4150 %
<b>Total volatiles volume percent</b>	39.7935 %

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Acids, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Formaldehyde. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Causes severe skin burns.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	> 2000 mg/kg ( Rat )		

ETHYLENE GLYCOL 107-21-1	4000 - 10200 mg/kg ( Rat )	= 9530 µL/kg ( Rabbit ) = 10600 mg/kg ( Rat )	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )		
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE 25265-77-4	= 3200 mg/kg ( Rat )	> 15200 mg/kg ( Rat )	
NONIONIC SURFACTANT 9036-19-5	= 4190 mg/kg ( Rat ) = 1700 mg/kg ( Rat )		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin burns. Eye Damage.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Corrosivity** May be corrosive to metals.  
**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

**Sensitization** No information available.  
**Mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8		Group 1	Known	
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B		X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X

**Reproductive effects** No information available.  
**STOT - single exposure** No information available  
**STOT - repeated exposure** No information available  
**Aspiration hazard** No information available.

**Acute Toxicity** 51.64550682 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

56.1073 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8			140 - 2000: 24 h Daphnia magna mg/L EC50
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	

ETHYLENE GLYCOL 107-21-1	6500 - 13000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41000: 96 h Oncorhynchus mykiss mg/L LC50 16000: 96 h Poecilia reticulata mg/L LC50 static 14 - 18: 96 h Oncorhynchus mykiss mL/L LC50 static 40000 - 60000: 96 h Pimephales promelas mg/L LC50 static 27540: 96 h Lepomis macrochirus mg/L LC50 static 40761: 96 h Oncorhynchus mykiss mg/L LC50 static	46300: 48 h Daphnia magna mg/L EC50
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE 25265-77-4	18.4: 72 h Pseudokirchneriella subcapitata mg/L EC50	30: 96 h Pimephales promelas mg/L LC50	95: 96 h Daphnia magna mg/L LC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
ETHYLENE GLYCOL 107-21-1	-1.93
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE 25265-77-4	3.47

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	CAWAST
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	Toxic Corrosive

**14. TRANSPORT INFORMATION**

**DOT**

Proper Shipping Name paint, water base freezable

**IATA**

Proper Shipping Name Not regulated

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
DSL/NDSL Complies

<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Does not comply
<b>PICCS</b>	Complies
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Component</b>	<b>HAPS Data</b>
COAL FIRED FLY ASH BI-PRODUCT	
ETHYLENE GLYCOL	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
COAL FIRED FLY ASH BI-PRODUCT - 68131-74-8	1.0 0.1
ETHYLENE GLYCOL - 107-21-1	1.0

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8		X		

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
ETHYLENE GLYCOL 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
COAL FIRED FLY ASH BI-PRODUCT - 68131-74-8	Carcinogen
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent



**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	X		X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
ETHYLENE GLYCOL 107-21-1	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 3	Flammability 1	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 3*	Flammability 1	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 19-Jun-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 19-Jun-2015

Revision Date 19-Jun-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F130-6602B  
**Product Name** ENVIROFILL OFF WHITE PART B

### Other means of identification

**Common Name** SERIES 130 PART B

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address**  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1


### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Harmful if swallowed  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye damage  
May cause an allergic skin reaction  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure  
May be corrosive to metals



**Appearance** opaque

**Physical state** liquid

**Odor** Slight

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Wear protective gloves/protective clothing/eye protection/face protection
- Contaminated work clothing should not be allowed out of the workplace
- Do not breathe dust/fume/gas/mist/vapors/spray

**Response**

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- IF ON SKIN: Wash with plenty of soap and water
- Take off contaminated clothing and wash before reuse
- If skin irritation or rash occurs: Get medical advice/attention
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth

**Storage**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs  
 Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns  
 SEE SAFETY DATA SHEET

Acute Toxicity 95.02 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
CALCIUM SILICATES AND ALUMINATES	65997-15-1	60 - 100%
IRON OXIDE FUME	1309-37-1	10 - 30%
GYPSUM	13397-24-5	1 - 10%
MAGNESIUM OXIDE	1309-48-4	1 - 10%
LIMESTONE	1317-65-3	1 - 10%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	1 - 10%
CALCIUM OXIDE	1305-78-8	1 - 10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

##### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** Shovel or sweep up.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. Tightly fitting safety goggles. Wear protective gloves/clothing. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep away from heat, sparks and flame. Keep container tightly closed.

**Incompatible products** Acids. Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM SILICATES AND ALUMINATES 65997-15-1	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
IRON OXIDE FUME 1309-37-1	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>  TWA: 15 mg/m <sup>3</sup>	2500 mg/m <sup>3</sup>
GYPSUM 13397-24-5	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	
MAGNESIUM OXIDE 1309-48-4	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	750 mg/m <sup>3</sup>
LIMESTONE 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
CALCIUM OXIDE 1305-78-8	TWA: 2 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	25 mg/m <sup>3</sup>

#### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tightly fitting safety goggles

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
pH		No data available	
Melting point / freezing point		No data available	
Boiling point / boiling range		No information available	
Flash point	No information available		
Evaporation rate		No data available	
Flammability (solid, gas)		Not applicable	
Flammability Limit in Air		No data available	
Upper flammability limit	N/A		
Lower flammability limit	N/A		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	3.15612	g/cm <sup>3</sup>	
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

**Other Information**

<b>Density</b>	26.32202 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	0 lbs/gal
<b>Total volatiles weight percent</b>	0 %
<b>Total volatiles volume percent</b>	0 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Acids, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure**

- Inhalation** HARMFUL BY INHALATION. Inhalation of dust in high concentration may cause irritation of respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
- Eye contact** Corrosive to the eyes and may cause severe damage including blindness.
- Skin contact** May cause sensitization by skin contact.
- Ingestion** Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
IRON OXIDE FUME 1309-37-1	> 10000 mg/kg ( Rat )		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		
CALCIUM OXIDE 1305-78-8	= 500 mg/kg ( Rat )		

**Information on toxicological effects**

**Symptoms** Skin disorders. Respiratory disorders. Eye Damage.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** Avoid repeated exposure. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).  
**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
IRON OXIDE FUME 1309-37-1		Group 3		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X

**Reproductive effects** No information available.  
**STOT - single exposure** Eyes, Respiratory system  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Eyes, respiratory system, Skin.  
**Aspiration hazard** Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

**Acute Toxicity** 95.02 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

84 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
CALCIUM OXIDE 1305-78-8		1070: 96 h Cyprinus carpio mg/L LC50 static	

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media****Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	CAWAST
CALCIUM SILICATES AND ALUMINATES 65997-15-1	Special
CALCIUM OXIDE 1305-78-8	Corrosive

**14. TRANSPORT INFORMATION****DOT**

Proper Shipping Name

CEMENT, PORTLAND (ITEM 42130)

**IATA**

Proper Shipping Name

Not regulated

**Additional information**

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION****International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances



**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen

**California SCAQMD Rule 443**

Does Not Contain Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
CALCIUM SILICATES AND ALUMINATES 65997-15-1	X	X	X
IRON OXIDE FUME 1309-37-1	X	X	X
GYPSUM 13397-24-5	X		X
MAGNESIUM OXIDE 1309-48-4	X	X	X
LIMESTONE 1317-65-3	X	X	X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
CALCIUM OXIDE 1305-78-8	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 0	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 1*	Flammability 0	Reactivity 1	

Prepared By  
 Revision Date  
 Revision Summary  
 9 4 5 7 10 8 11 14


Tnemec Regulatory Dept: 816-474-3400  
 19-Jun-2015

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date No data available

Revision Date 02-Jun-2015

Revision Number 4

## 1. IDENTIFICATION

### Product identifier

Product Code F130-0130C  
Product Name ENVIROFILL PART C

### Other means of identification

Common Name SERIES 130 PART C

### Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.  
Uses advised against Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

Manufacturer Address  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

### Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400  
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1B
Skin sensitization	Category 1B

### Label elements

#### EMERGENCY OVERVIEW

#### WARNING

#### Hazard statements

Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction



Appearance opaque

Physical state liquid

Odor Slight

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 In case of inadequate ventilation wear respiratory protection  
 Contaminated work clothing should not be allowed out of the workplace  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation or rash occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse  
 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing  
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
CITRIC ACID	77-92-9	30 - 60%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

Notes to physician Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical. Water.

**Unsuitable extinguishing media** No information available.

### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong bases. Strong oxidizing agents. Heavy metals.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

#### Appropriate engineering controls

#### Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

##### Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

##### Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

#### General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		

#### Property

#### Values

#### Remarks

pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	100 °C / 212.0 °F	No information available
Flash point	No information available	
Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.24329	g/cm <sup>3</sup>
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

#### Other Information

Density	10.36903 lbs/gal
---------	------------------

Volatile organic compounds (VOC) 0 lbs/gal  
 content  
 Total volatiles weight percent 50 %  
 Total volatiles volume percent 62.24 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong bases, Strong oxidizing agents, Heavy metals

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	Avoid breathing vapors or mists. May cause sensitization of susceptible persons.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CITRIC ACID 77-92-9	= 3000 mg/kg ( Rat )		

### Information on toxicological effects

**Symptoms** Skin disorders. Respiratory disorders. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Chronic Toxicity</b>	Avoid repeated exposure.
<b>Sensitization</b>	May cause sensitization of susceptible persons.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	No information available.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

50 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
CITRIC ACID 77-92-9		1516: 96 h Lepomis macrochirus mg/L LC50 static	120: 72 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
CITRIC ACID 77-92-9	-1.72

**Other Adverse Effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**DOT**

Proper Shipping Name

PAINT & RELATED MATERIAL-(NMFC 149980 SUB 2)

**IATA**

Proper Shipping Name

Not regulated

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances



ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Does Not Contain Photochemically Reactive Solvent

**State Right-to-Know**

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health 2	Flammability 0	Instability 0	Physical hazard -
<b><u>HMIS (Hazardous Material Information System)</u></b>	Health 2	Flammability 0	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 02-Jun-2015  
 Revision Summary  
 9 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**