



Safety Data Sheet

Issue Date 22-Sep-2015

Revision Date 22-Sep-2015

Revision Number 4

1. IDENTIFICATION

Product identifier

Product Code S206-33GRA
Product Name SUB-FLEX EP GRAY

Other means of identification

Common Name SERIES 206 or 206SC, PART A

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO
64120-1372

Distributor

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203
Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1


Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes severe skin burns and eye damage
May cause an allergic skin reaction
Suspected of causing cancer
Causes damage to organs through prolonged or repeated exposure
May be corrosive to metals



Appearance opaque
Physical state liquid
Odor Slight

Precautionary Statements

Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Do not breathe dust/fume/gas/mist/vapors/spray
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Do not eat, drink or smoke when using this product

Response

- Immediately call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- If skin irritation or rash occurs: Get medical advice/attention
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Immediately call a POISON CENTER or doctor/physician
- IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Storage

- Store locked up
- Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

Toxic to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET
 Acute Toxicity 57.81418049 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	1 - 10%
TALC (RESPIRABLE DUST)	14807-96-6	1 - 10%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice If symptoms persist, call a physician.

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Aldehydes. Hydrogen cyanide.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Acids. Bases. Amines. Strong oxidizing agents. Hypochlorites. Peroxides.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

- Eye/face protection** Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
- Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range		No information available
Flash point		No information available
Evaporation rate		No data available
Flammability (solid, gas)		No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.19844	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	2930 centipoises	approx

Other Information

Density	9.995 lbs/gal
Volatile organic compounds (VOC) content	0.06097 lbs/gal
Total volatiles weight percent	0.61 %
Total volatiles volume percent	0.87 %

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Amines.

Incompatible materials

Acids, Bases, Amines, Strong oxidizing agents, Hypochlorites, Peroxides

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Hydrogen cyanide. Carbon oxides. Hydrocarbons. Aldehydes.

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure**

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Eye contact	Causes serious eye damage.
Skin contact	Causes severe skin burns. May cause sensitization by skin contact.

Ingestion

Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)		

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Corrosivity Causes severe damage to eyes and skin. May be corrosive to metals.
Chronic Toxicity May cause cancer. Skin sensitizer.
Sensitization May cause sensitization of susceptible persons.
Mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B		X
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		

Reproductive effects No information available.
STOT - single exposure No information available
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects Central Vascular System (CVS), Eyes, Lungs, respiratory system, Skin.
Aspiration hazard No information available.

Acute Toxicity 57.81418049 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

0.97401 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media**Other Adverse Effects**

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods**Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name paint in oil Not regulated

IATA

Proper Shipping Name Not regulated

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Does not comply
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Does not comply
AICS	Does not comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA

United States of America

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
TALC (RESPIRABLE DUST) - 14807-96-6	*

California SCAQMD Rule 443

Does Not Contain Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X

16. OTHER INFORMATION

NFPA	Health 3	Flammability 0	Instability 0	Physical hazard *
HMIS (Hazardous Material Information System)	Health 3*	Flammability 0	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 22-Sep-2015

Revision Summary
 9 4 5 7 10 8 11 14 15 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 23-Sep-2015

Revision Date 23-Sep-2015

Revision Number 7

1. IDENTIFICATION

Product identifier

Product Code S206-0206B
Product Name SUB-FLEX EP CONVERTER

Other means of identification

Common Name SERIES 206 OR 206SC, PART B
UN/ID no. 3066

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Harmful if swallowed
 Harmful in contact with skin
 Causes severe skin burns and eye damage
 May cause allergy or asthma symptoms or breathing difficulties if inhaled
 May cause an allergic skin reaction
 Suspected of damaging fertility or the unborn child
 Causes damage to organs through prolonged or repeated exposure
 May be corrosive to metals

**Appearance** opaque**Physical state** liquid**Odor** amine**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Do not breathe dust/fume/gas/mist/vapors/spray
 In case of inadequate ventilation wear respiratory protection
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves

Response

Immediately call a POISON CENTER or doctor/physician
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 Call a POISON CENTER or doctor/physician if you feel unwell
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 If skin irritation or rash occurs: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Immediately call a POISON CENTER or doctor/physician
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth
 Do NOT induce vomiting

Storage

Store locked up
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

Acute Toxicity 5.43937 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
NONYLPHENOL	84852-15-3	30 - 60%
MODIFIED ALIPHATIC AMINE	9046-10-0	30 - 60%
MODIFIED ALIPHATIC AMINE	140-31-8	10 - 30%
BENZYL ALCOHOL	100-51-6	1 - 10%
AMINE POLYMER	-	1 - 10%
MODIFIED ALIPHATIC AMINE	1761-71-3	1 - 10%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Ammonia. Nitric acid, nitrosamine. Ketones. Phenolics.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Water, alcohols, amines, strong bases, metal components, surface active materials. Acids. Strong oxidizing agents. Hypochlorites. Nitrous acid and other nitrosating agents. Peroxides. Hydroxyl Compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.
Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	amine
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	72 °C / 162 °F	
Flash point	No information available	
Evaporation rate		No data available
Flammability (solid, gas)		No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.96541	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	115 centipoises	approx

Other Information

Density	8.05155 lbs/gal
Volatile organic compounds (VOC) content	0.09742 lbs/gal
Total volatiles weight percent	1.21 %
Total volatiles volume percent	1.23 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Epoxy constituents.

Incompatible materials

Water, alcohols, amines, strong bases, metal components, surface active materials, Acids, Strong oxidizing agents, Hypochlorites, Nitrous acid and other nitrosating agents, Peroxides, Hydroxyl Compounds

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Nitric acid, nitrosamine. Oxides of nitrogen. Aldehydes. Ammonia. Ketones. Phenolics.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	May cause irritation. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Causes serious eye damage.
Skin contact	Causes severe skin burns. May cause sensitization by skin contact.
Ingestion	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
NONYLPHENOL 84852-15-3	= 1300 mg/kg (Rat)	= 2031 mg/kg (Rabbit)	
MODIFIED ALIPHATIC AMINE 9046-10-0	= 242 mg/kg (Rat)	= 360 mg/kg (Rabbit)	
MODIFIED ALIPHATIC AMINE 140-31-8	= 2140 µL/kg (Rat)	= 880 µL/kg (Rabbit)	
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg (Rat)	= 2 g/kg (Rabbit)	= 8.8 mg/L (Rat) 4 h
MODIFIED ALIPHATIC AMINE 1761-71-3	= 1000 mg/kg (Rat)		

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin. Respiratory disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Corrosivity Causes severe damage to eyes and skin. May be corrosive to metals.
Chronic Toxicity NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Substances known to impair fertility. May cause sensitization by inhalation and skin contact.
Sensitization May cause sensitization of susceptible persons.
Mutagenicity No information available.
Carcinogenicity There are no known carcinogenic chemicals in this product.
Reproductive effects Suspected of damaging fertility or the unborn child.
STOT - single exposure No information available
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure, kidney, liver, Respiratory system, EYES, Skin, Central Nervous System (CNS), Gastrointestinal tract (GI)
Aspiration hazard No information available.
Acute Toxicity 5.43937 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

36.67891 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
NONYLPHENOL 84852-15-3	0.36 - 0.48: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.16 - 0.72: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.3: 72 h Desmodesmus subspicatus mg/L EC50	0.135: 96 h Pimephales promelas mg/L LC50 flow-through 0.1351: 96 h Lepomis macrochirus mg/L LC50 flow-through	0.14: 48 h Daphnia magna mg/L EC50

MODIFIED ALIPHATIC AMINE 140-31-8	495: 72 h Pseudokirchneriella subcapitata mg/L EC50	1950 - 2460: 96 h Pimephales promelas mg/L LC50 flow-through 1000: 96 h Poecilia reticulata mg/L LC50 semi-static 100: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	32: 48 h Daphnia magna mg/L EC50
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	460: 96 h Pimephales promelas mg/L LC50 static 10: 96 h Lepomis macrochirus mg/L LC50 static	23: 48 h water flea mg/L EC50
MODIFIED ALIPHATIC AMINE 1761-71-3		46 - 100: 96 h Leuciscus idus mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Component	log Pow
NONYLPHENOL 84852-15-3	5.4
MODIFIED ALIPHATIC AMINE 140-31-8	-1.48
BENZYL ALCOHOL 100-51-6	1.1
MODIFIED ALIPHATIC AMINE 1761-71-3	2.03

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION**DOT**

UN/ID no. 3066
 Proper Shipping Name paint
 Hazard Class 8
 Packing Group II
 Emergency Response Guide Number 153

IATA

UN/ID no. 3066
 Proper Shipping Name paint
 Hazard Class 8
 Packing Group II
 ERG Code 855

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

United States of America**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
NONYLPHENOL - 84852-15-3	1.0

SARA 311/312 Hazardous**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA**United States of America****California Prop. 65**

This product does not contain any Proposition 65 chemicals

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
MODIFIED ALIPHATIC AMINE 140-31-8	X	X	X
BENZYL ALCOHOL 100-51-6		X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health 3	Flammability 0	Instability 0	Physical hazard -
<u>HMIS (Hazardous Material Information System)</u>	Health 3	Flammability 0	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 23-Sep-2015


Revision Summary
9 4 5 7 10 8 11 14 15 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date No data available

Revision Date 27-Jan-2015

Revision Number 4

1. IDENTIFICATION

Product identifier

Product Code S211-0214
Product Name FUMED SILICA S C MORTAR

Other means of identification

Common Name SERIES 211-214

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1


Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Harmful if swallowed
Harmful if inhaled
Causes serious eye irritation
May cause cancer
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure



Appearance light grey
Physical state powder
Odor odorless

Precautionary Statements

Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray

Response

- IF exposed: Call a POISON CENTER or doctor/physician
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth

Storage

- Store locked up
- Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).
 Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs
 SEE SAFETY DATA SHEET
 Acute Toxicity 0.000102 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	30 - 60%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	30 - 60%
COAL FIRED FLY ASH BI-PRODUCT	68131-74-8	1 - 10%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

- General advice** If symptoms persist, call a physician.
- Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up Shovel or sweep up.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. Tightly fitting safety goggles. Wear protective gloves/clothing. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	50 mg/m ³
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	50 mg/m ³
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	TWA: 1 mg/m ³	-	100 mg/m ³ 10 mg/m ³

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

- Eye/face protection** Use chemical resistant splash type goggles.
- Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	powder	Odor	odorless
Appearance	light grey	Odor threshold	No information available
Color	No information available		
Property	Values	Remarks	
pH		No data available	
Melting point / freezing point		No data available	
Boiling point / boiling range	72 °C / 162 °F		
Flash point	No information available		

Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	2.34955	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

Other Information

Density	19.59523 lbs/gal
Volatile organic compounds (VOC) content	0 lbs/gal
Total volatiles weight percent	0 %
Total volatiles volume percent	0 %

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Incompatible with oxidizing agents

Hazardous decomposition productsHazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide (CO₂). Hydrocarbons.**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

Inhalation	Harmful if inhaled. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Eye contact	Severely irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg (Rat)		

CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg (Rat)		
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	> 2000 mg/kg (Rat)		

Information on toxicological effects

Symptoms Respiratory disorders. Eye Damage.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

Sensitization No information available.

Mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8		Group 1	Known	

Reproductive effects No information available.

STOT - single exposure Eyes, Respiratory system

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure

Target organ effects blood, Central nervous system, Central Vascular System (CVS), Eyes, kidney, liver, Lungs, Nasal Cavities, prostate, respiratory system, Skin.

Aspiration hazard Not applicable.

Acute Toxicity 0.000102 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

98.08407 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8			140 - 2000: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media**Other Adverse Effects**

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	CAWAST
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	Toxic Corrosive

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name SILICA, N.O.I.-20-P.C.F., GREATER (ITEM 176370, SUB 3)

IATA

Proper Shipping Name Not regulated

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
COAL FIRED FLY ASH BI-PRODUCT	

United States of America**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
COAL FIRED FLY ASH BI-PRODUCT - 68131-74-8	1.0 0.1

SARA 311/312 Hazardous**Categorization**

Acute Health Hazard Yes

Chronic Health Hazard Yes
 Fire Hazard No
 Sudden Release of Pressure Hazard No
 Reactive Hazard No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8		X		

CERCLA

United States of America

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
COAL FIRED FLY ASH BI-PRODUCT - 68131-74-8	Carcinogen

California SCAQMD Rule 443

Does Not Contain Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	X		X

16. OTHER INFORMATION

NFPA Health 1 Flammability 0 Instability 0 Physical hazard *
HMIS (Hazardous Material Information System) Health 1* Flammability 0 Reactivity 0

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 27-Jan-2015
 Revision Summary
 9 4 5 7 10 8 11 14

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS