



# Safety Data Sheet

Issue Date 28-Nov-2018

Revision Date 28-Nov-2018

Revision Number 2

## 1. IDENTIFICATION

### Product identifier

**Product Code** F489-0904A  
**Product Name** LAVACRETE MEDIUM GRAY

### Other means of identification

**Common Name** SERIES 489, PART A  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor



**Appearance** opaque

**Physical state** liquid

**Odor** pungent

**Precautionary Statements**

**Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

Harmful to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 May form combustible dust concentrations in air  
 If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	60 - 100%
COBALT NAPHTHANATE	61789-51-3	1 - <10%

HEAVY NAPHTHA (HYDROTREATED)	64742-48-9	1 - <10%
ALUMINUM OXIDES	1344-28-1	1 - <10%
CARBON BLACK DUST & FUME	1333-86-4	1 - <10%
AMORPHOUS SILICA	7631-86-9	1 - <10%
2,4-PENTANEDIONE	123-54-6	1 - <10%
ZIRCONIUM OXIDE	1314-23-4	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Hydrocarbons. Carbon oxides.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or

sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** Pick up and transfer to properly labelled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Remove and wash contaminated clothing before re-use. Avoid contact with eyes, skin and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Acids. Strong oxidizing agents. Strong bases. Aluminum. copper. Halogenated compounds. Metal salts. Peroxides.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
ALUMINUM OXIDES 1344-28-1	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	
CARBON BLACK DUST & FUME 1333-86-4	TWA: 3 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	1750 mg/m <sup>3</sup>
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m <sup>3</sup>	3000 mg/m <sup>3</sup>
2,4-PENTANEDIONE 123-54-6	TWA: 25 ppm Skin	-	
ZIRCONIUM OXIDE 1314-23-4	TWA: 5 mg/m <sup>3</sup>	-	25 mg/m <sup>3</sup>

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tightly fitting safety goggles

<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	pungent
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	145 °C / 293 °F	
<b>Flash point</b>	26.0 °C / 78.8 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	NA	
<b>Lower flammability limit</b>	NA	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.08352	g/cm3
<b>Water solubility</b>	insoluble	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>	>20.5 mm2/s	@ 40 °C
<b>Explosive properties</b>	May form combustible dust concentrations in air.	

### Other Information

<b>Density</b>	9.03653 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	0.03886 lbs/gal
<b>Total volatiles weight percent</b>	0.43 %
<b>Total volatiles volume percent</b>	0.58 %
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

May form combustible dust concentrations in air. Vapors may form explosive mixtures with air.

**Hazardous polymerization** Hazardous polymerization may occur.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Acids, Strong oxidizing agents, Strong bases, Aluminum, copper, Halogenated compounds, Metal salts, Peroxides

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

**Inhalation** May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

**Eye contact** Causes serious eye irritation.

**Skin contact** Irritating to skin.

**Ingestion** Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )	-	-
COBALT NAPHTHANATE 61789-51-3	= 3900 mg/kg ( Rat )	-	-
HEAVY NAPHTHA (HYDROTREATED) 64742-48-9	> 6000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	> 8500 mg/m <sup>3</sup> ( Rat ) 4 h
ALUMINUM OXIDES 1344-28-1	> 5000 mg/kg ( Rat )	-	-
CARBON BLACK DUST & FUME 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
2,4-PENTANEDIONE 123-54-6	= 55 mg/kg ( Rat ) = 570 mg/kg ( Rat ) = 760 mg/kg ( Rat )	= 1370 mg/kg ( Rabbit ) = 790 mg/kg ( Rabbit ) = 810 µL/kg ( Rabbit )	= 1224 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Irritating to eyes and skin. May cause eye and respiratory irritation.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** Substances known to be carcinogenic to man.  
**Sensitization** No information available.  
**Mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
COBALT NAPHTHANATE 61789-51-3		Group 2B	Reasonably Anticipated	X
CARBON BLACK DUST & FUME	A3	Group 2B	-	X

1333-86-4			
AMORPHOUS SILICA 7631-86-9		Group 1 Group 3	Known

**Reproductive effects** No information available.  
**STOT - single exposure** Causes damage to organs  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Eyes, respiratory system, Skin, hearing.  
**Aspiration hazard** No information available.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects

13.19403 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
HEAVY NAPHTHA (HYDROTREATED) 64742-48-9		2200: 96 h Pimephales promelas mg/L LC50	2.6: 96 h Chaetogammarus marinus mg/L LC50
CARBON BLACK DUST & FUME 1333-86-4			5600: 24 h Daphnia magna mg/L EC50
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
2,4-PENTANEDIONE 123-54-6		50.3 - 71.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 98.3 - 110: 96 h Pimephales promelas mg/L LC50 flow-through 64.1 - 80.1: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	34.4: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
2,4-PENTANEDIONE 123-54-6	0.34

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### Disposal Methods

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

#### Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

### California Hazardous Waste Status

Not applicable

Chemical name	CAWAST
COBALT NAPHTHANATE	Toxic

61789-51-3	
------------	--

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Does Not Comply  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

Chemical name	HAPS Data
COBALT NAPHTHANATE	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
COBALT NAPHTHANATE - 61789-51-3	1.0
ALUMINUM OXIDES - 1344-28-1	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**California Prop. 65**



**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
CARBON BLACK DUST & FUME - 1333-86-4	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
COBALT NAPHTHANATE 61789-51-3	X		X
ALUMINUM OXIDES 1344-28-1	X	X	X
CARBON BLACK DUST & FUME 1333-86-4	X	X	X
AMORPHOUS SILICA 7631-86-9		X	X
2,4-PENTANEDIONE 123-54-6	X	X	X
ZIRCONIUM OXIDE 1314-23-4		X	

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 2 Physical hazard -  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 3 Reactivity 2


**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 28-Nov-2018  
**Revision Summary**  
 1 9 5 6 7 10 8 11 13 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 26-Oct-2018

Revision Date 26-Oct-2018

Revision Number 3

## 1. IDENTIFICATION

### Product identifier

**Product Code** 1402-0001B  
**Product Name** PROPOLYMER CATALYST

### Other means of identification

**Common Name** SERIES 1402-1432, PART B  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Organic Peroxides	Type F
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### Danger

### Hazard statements

Toxic if inhaled  
Causes severe skin burns and eye damage  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Heating may cause a fire  
Flammable liquid and vapor

**Appearance** yellow**Physical state** liquid**Odor** Strong aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep only in original container  
 Keep cool  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment

**Response**

Immediately call a POISON CENTER or doctor/physician  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Immediately call a POISON CENTER or doctor/physician  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Store at temperatures not exceeding 38 °C/ 100 °F. Keep cool  
 Store away from other materials  
 Protect from sunlight  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
CUMENE HYDROPEROXIDE	80-15-9	60 - 100%
CUMYL ALCOHOL	617-94-7	1 - <10%
CUMENE (SKIN)	98-82-8	1 - <10%
ACETOPHENONE	98-86-2	1 - <10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Immediate medical attention is required.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
<b>Ingestion</b>	Immediate medical attention is required. Rinse mouth. Drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Remove all sources of ignition.

##### Most important symptoms and effects, both acute and delayed

<b>Most important symptoms and effects</b>	Causes burns to skin and eyes. MAY CAUSE BLINDNESS. Coughing and / or wheezing.
<b>Notes to physician</b>	Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Carbon dioxide. Dry chemical. Water spray. Foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Avoid run off to waterways and sewers.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment. Keep people away from and upwind of spill/leak.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** Pick up and transfer to properly labelled containers.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Use with local exhaust ventilation. Wear personal protective equipment. Do not breathe vapours or spray mist.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store at temperatures not exceeding 38 °C/ 100 °F. Keep cool. Do not store near combustible materials.

**Packaging materials** Keep only in original container.

**Incompatible products** Strong acids. Strong bases. Strong oxidizing agents. Amines. Metals. SALT. Reducing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CUMENE (SKIN) 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin	900 ppm
ACETOPHENONE 98-86-2	TWA: 10 ppm	-	

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Tightly fitting safety goggles If splashes are likely to occur, wear face-shield.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Strong aromatic
<b>Appearance</b>	yellow	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	> 100 °C / 212 °F	
<b>Flash point</b>	56 °C / 133.00 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>	< 1	
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	NA	
<b>Lower flammability limit</b>	NA	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.03118 1.0324	g/cm3
<b>Water solubility</b>	slightly soluble	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	No data available
<b>Decomposition temperature</b>	> 60° C	
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	8.60001 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	1.075 lbs/gal
<b>Total volatiles weight percent</b>	12.5 %
<b>Total volatiles volume percent</b>	12.3 %
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY****Reactivity**

Stable under normal conditions

**Chemical stability**

Stable under recommended storage conditions.

#### **Possibility of hazardous reactions**

Vapors may form explosive mixtures with air.

#### **Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition. Temperatures above 38°C.

#### **Incompatible materials**

Strong acids, Strong bases, Strong oxidizing agents, Amines, Metals, SALT, Reducing agents

#### **Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### **Information on Likely Routes of Exposure**

<b>Inhalation</b>	Irritating to respiratory system. May be harmful by inhalation. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Corrosive to the eyes and may cause severe damage including blindness.
<b>Skin contact</b>	Causes burns.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
CUMENE HYDROPEROXIDE 80-15-9	= 382 mg/kg ( Rat )	= 0.126 mL/kg ( Rabbit )	= 220 ppm ( Rat ) 4 h
CUMYL ALCOHOL 617-94-7	= 1300 mg/kg ( Rat )	= 1 mL/kg ( Rabbit ) = 4300 mg/kg ( Rabbit )	-
CUMENE (SKIN) 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h
ACETOPHENONE 98-86-2	= 815 mg/kg ( Rat ) = 900 mg/kg ( Rat )	= 1760 mg/kg ( Rabbit )	> 2.130 mg/L ( Rat ) 8 h

### **Information on toxicological effects**

**Symptoms** Avoid repeated exposure. MAY CAUSE BLINDNESS. Causes severe skin burns. Coughing and/ or wheezing.

### **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	Causes severe burns.
<b>Eye damage/irritation</b>	Risk of serious damage to eyes.
<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid repeated exposure. Causes burns to skin and eyes. Aspiration hazard.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
CUMENE (SKIN) 98-82-8		Group 2B	Reasonably Anticipated	X

<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure
<b>Target organ effects</b>	Eyes, respiratory system, Skin, Central nervous system.
<b>Aspiration hazard</b>	May be harmful if swallowed and enters airways.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

6 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
CUMENE HYDROPEROXIDE 80-15-9		3.9: 96 h Oncorhynchus mykiss mg/L LC50 static	7: 24 h Daphnia magna mg/L EC50
CUMENE (SKIN) 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static 6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static 0.6: 48 h Daphnia magna mg/L EC50
ACETOPHENONE 98-86-2		162: 96 h Pimephales promelas mg/L LC50 flow-through 155: 96 h Pimephales promelas mg/L LC50 static	

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
CUMENE (SKIN) 98-82-8	3.55
ACETOPHENONE 98-86-2	1.58

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

#### **Contaminated packaging**

Do not reuse container. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### **US EPA Waste Number**

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
CUMENE HYDROPEROXIDE 80-15-9				U096
CUMENE (SKIN) 98-82-8				U055
ACETOPHENONE 98-86-2	U004	Included in waste stream: F039		U004

### **California Hazardous Waste Status**



Chemical name	CAWAST
CUMENE HYDROPEROXIDE 80-15-9	Toxic Ignitable
CUMENE (SKIN) 98-82-8	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
CUMENE (SKIN)	
ACETOPHENONE	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
CUMENE HYDROPEROXIDE - 80-15-9	1.0
CUMENE (SKIN) - 98-82-8	1.0
ACETOPHENONE - 98-86-2	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes

Sudden Release of Pressure Hazard No  
 Reactive Hazard No

**CERCLA**

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
CUMENE HYDROPEROXIDE 80-15-9	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
CUMENE (SKIN) 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ACETOPHENONE 98-86-2	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
CUMENE (SKIN) - 98-82-8	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
CUMENE HYDROPEROXIDE 80-15-9	X	X	X
CUMENE (SKIN) 98-82-8	X	X	X
ACETOPHENONE 98-86-2	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 3 Flammability 2 Instability 1 Physical hazard -  
**HMIS (Hazardous** Health 3\* Flammability 2 Reactivity 1  
**Material Information**  
**System)**

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 26-Oct-2018


Revision Summary  
 1 9 4 5 6 7 10 8 11 13 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 02-Jul-2019

Revision Date 02-Jul-2019

Revision Number 4

## 1. IDENTIFICATION

### Product identifier

**Product Code** F469-0489C  
**Product Name** LAVACRETE AGGREGATE

### Other means of identification

**Common Name** SERIES 469/479/489, PART C  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

May cause cancer  
Causes damage to organs through prolonged or repeated exposure



**Appearance** powder

**Physical state** powder

**Odor** No information available

**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product

**Response**

IF exposed or concerned: Get medical advice/attention

**Storage**

Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

May form combustible dust concentrations in air

**Other information**

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs

SEE SAFETY DATA SHEET

Acute Toxicity 93.746695 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician.
<b>Ingestion</b>	Rinse mouth. Clean mouth with water and drink afterwards plenty of water. If symptoms persist, call a physician. Do NOT induce vomiting.
<b>Self-protection of the first aider</b>	Use personal protective equipment.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Methanol.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment. Avoid dust formation. Evacuate personnel to safe areas. Avoid contact with eyes, skin and clothing. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage if safe to do so.

**Methods for cleaning up** Use personal protective equipment. Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Avoid contact with eyes, skin and clothing. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Fine dust dispersed in air may ignite. Avoid dust formation.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Hydrogen fluoride. Strong bases. Strong oxidizing agents. Acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup>	50 mg/m <sup>3</sup>

**Legend**

NIOSH IDLH: *Immediately Dangerous to Life or Health*

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product. Provide readily accessible eye wash stations and safety showers.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Chemical goggles or safety glasses with side-shields.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	powder	<b>Odor</b>	No information available
<b>Appearance</b>	powder	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>	No data available		
<b>Boiling point / boiling range</b>		No information available	
<b>Flash point</b>	No information available		
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>	No data available		
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	NA		
<b>Lower flammability limit</b>	NA		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	2.525342	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>	No data available	No data available	
<b>Decomposition temperature</b>	No information available	No data available	
<b>Kinematic viscosity</b>	No information available	No data available	
<b>Dynamic viscosity</b>		No data available	
<b>Explosive properties</b>	May form combustible dust concentrations in air.		

**Other Information**

<b>Molecular weight</b>	No information available
<b>Density</b>	21.03611 lbs/gal

**Volatile organic compounds (VOC) content** 0 lbs/gal  
**Total volatiles weight percent** 0 %  
**Total volatiles volume percent** 0 %  
**Bulk density** No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**  
 No data available

**Chemical stability**  
 Stable under recommended storage conditions.

**Possibility of hazardous reactions**  
 May form combustible dust concentrations in air.

**Conditions to avoid**  
 Avoid dust formation.

**Incompatible materials**  
 Hydrogen fluoride, Strong bases, Strong oxidizing agents, Acids

**Hazardous decomposition products**  
 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Methanol.

**11. TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure**

**Inhalation** May cause irritation of respiratory tract. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

**Eye contact** May cause irritation.

**Skin contact** May cause irritation.

**Ingestion** May be harmful if swallowed.

**Information on toxicological effects**

**Symptoms** Respiratory disorders.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X

**Legend:**  
 ACGIH: (American Conference of Governmental Industrial Hygienists)  
 A2 - Suspected Human Carcinogen  
 IARC: (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 NTP: (National Toxicity Program)

*Known - Known Carcinogen*

*OSHA: (Occupational Safety & Health Administration)*

*X - Present*

<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure
<b>Target organ effects</b>	Lungs, respiratory system, Eyes.
<b>Aspiration hazard</b>	No information available.
<b>Acute Toxicity</b>	93.746695 % of the mixture consists of ingredient(s) of unknown toxicity.
<b>ATEmix (oral)</b>	5000 mg/kg

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

None known

93.8849 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

### **Disposal Methods**

In accordance with local and national regulations.

### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not reuse container.

## 14. TRANSPORT INFORMATION

### DOT

#### **Proper Shipping Name**

Paint related material NOT REGULATED

### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies



PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen

**California SCAQMD Rule 443**

Does Not Contain Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 0	Instability 0	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 1*	Flammability 0	Reactivity 0	

Chronic Hazard Star Legend                      \* = Chronic Health Hazard

Prepared By    Tnemec Regulatory Dept: 816-474-3400  
 Revision Date    02-Jul-2019  
 Revision Summary  
 1 9 4 5 6 7 10 8 11 13 14 15 3

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained

herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**